

FEB 18 1994

COMMISSION

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

KALKASKA

(County)

1993 REMONUMENTATION

Located In:

Corner Code ~~##~~

1. Public Land Survey

T 27N R 7W

K-9

2. Property Controlling  
in Section

S T R

3. Miscellaneous  
Property in Sec.

S T R

4. Lot No. , Recorded Plat

5. Private Claims

KALKASKA COUNTY, MICHIGAN  
RECEIVED

1993 DEC 22 PM 1:33

Joan Hare  
REG. OF DEEDS

Register of Deeds Stamp & File Number

I, EUGENE FARRIER, in a field survey on DEC. 7, 19 93,  
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned  
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the  
current manual of survey instructions of the United States Department of the Interior, Bureau of Land  
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5  
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a  
Court of Law; established, re-established, monumented, re-monumented, recovered, found as  
expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded  
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

K-9 cor. common to Sec. 23, 24, 25 & 26, T27N-R7W  
1850 GLO re-survey: set post, Beech 8", N88E, 30; Beech 18", S72W, 55.  
12-3-1885, E. Mosher, Co. Surv., used cor. for survey in NW/4 Sec. 25.  
4-10-03, W.S. Merrill, Co. Surv., iron gas pipe, NE cor. of Schoolhouse  
wall S33W, 84.61 feet.  
8-22-07, W.S. Merrill, Co. Surv., iron stake.  
MSHD, survey for M-72, tied corner.  
9-13-71, P.G. Perla, fd angle iron, set 5/8" rod, Liber 1 Pg 46.  
6-15-73, P.G. Perla, fd 5/8" iron rod, Liber 1 Pg 341.  
4-30-74, L.J. Czubak, fd 5/8" iron rod, Liber 1 Pg 545.  
5-21-75, LCRC Liber 1 Pg 351.  
7-77, A.L. Dragoo, fd iron rod in Mon. Box, Liber 2 Pg 30.  
4-28-78, L.M. Gerschbacher, survey for Shell Oil Company.  
8-28-87, N.B. DeYoung, fd 5/8" rod in Mon. Box, Liber 3 Pg 161 of Surv.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

K-9 cor. common to Sec. 23, 24, 25 & 26, T27N-R7W  
Found 5/8" re-bar in Mon. box in C/L M-72, 9'+/- E. of C/L Aller road N.  
and 4'+/- E. of C/L Golden road S.  
On 12-16-93 the Kalkaska Co. peer group approved the above monument as a  
careful and faithful reestablishment of the position of the original  
corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

K-9 cor. common to Sec. 23, 24, 25 & 26, T27N-R7W  
Found 5/8" re-bar in Mon. Box set w/ Brass Cap.  
S40W, 92.0', NE cor. old Stone School Hse.  
S15W, 133.13', 12" Maple, W. side.  
S60W, 103.43', P. Pole, NW side.  
N15E, 76.13', P. Pole 6' high, W. side.

Signed by Eugene Farrier

Date 12-22-93

Surveyor's Michigan License No. 24594

