## LAND CORNER RECORDATION CERTIFICATE Filling Requirement of Act 74, Mich. P.A. 1970

For corners in			
KALKASKA (County)	Located In:	Corner Code #	SURVEY & REMONUMENTATION
2000 REMONUMENTATION 1. Public Land Survey	T <u>27N</u> R 8W_ TR	_A-11	FEB 26 2001
2. Property Controlling S	TR TR TR		SECTION
in Section S3. Miscellaneous S	TR TR		
Property in Sec. S	TR		
4. Lot No, Recorded Pla	ıt		
5. Private Claims			A B C D E F G H I J K L M
			2 6 5 4 3 2 1 1
I, FUGENE FARRIER , in a field so	urvey on <u>NOVEMBER</u>	, 20 <u>00</u> do hereby state	4 -7 - 8 - 9 - 10 - 11 - 12 - 5
that under requirements of P.A. 74, Michigen P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed			6 -18 - 17 - 16 - 15 - 14 - 13
			7
			9 - 19 - 20 - 21 - 22 - 23 - 24 - 9
below:			10 30 29 28 27 26 25
NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.		1 <del> </del>	
			12 31 32 33 34 35 36
A. Description of original monument and accessories and/or subsequent restoration:  A-11: Section corner common to Sections 30 and 31. T27N-R8W and Sections 25 and 36. T27N-R9W;  A Maple post witnessed by a Suger 8° S49°E, 44 links and White Pine 10" N 48°W, 30 links, U.S. resurvey by Lucius Lyon, dated 1850. Original Corner found, survey index by M. Schaaf, (State Surveyor), dated around 1930. Set 1" iron bar in a straight line and single proportionate between two recovered corners, Land Corner Certificate by J.L. Wilcox, dated 1-15-73 and recorded in Liber 1 Page 175 of the Land Corner Records Kalkaska County.			
8. Description of corner evidence found and/or method applied in restoring or reestabilishing corner:  A-11: Section corner common to Sections 30 and 31. T27N-R8W and Sections 25 and 36. T27N-R9W; Found 1"iron bar as recorded in Liber 1 Page 175 of the Kalkaska County Records, Found no evidence of the Schaaf monumentation as called for in his index or the U.S. bearing trees. Re-established this corner position to best satisfy the following conditions: (1) That the corner equalize best as possible each respective ½ mile on the East lines of Sections 25 and 36, and (2) That the corner be consistent with the U.S. stream call to the North, and (3) That the corner be in reasonable agreement with a fire lane constructed on the section line between Section 25 and 36, T27N-R9W and is accepted as a careful and faithful re-establishment of the position of the original corner. Monumented this position with a 2 1/2" x 30" flanged bottom galvanized iron pipe with 3 1/4" brass cap stanped GRAND TRAVERSE COUNTY REMONUMENTATION, 12" below the surface of the ground. 1" bar recorded in Liber 1 Page 175 of the Land Corner Records of Kalkaska County is located S 021°28'E 55.64'.			
LCRC by Robert F. Mitchell December 28, Pine, 9.14'; N 46°W, 14" Red Pine, 18.2			78; N 01°E, 13" Red Pine, 25.27'; N84°E, Jack 55.64'.
Corner approved by the Grand Traverse County Peer Review Group on 12-15-93.			
C. Description of monument for corner of A-11: Section corner common to Sector Found standard Grand Traverse County mon No1°E - 13" Red Pine - 25.27" N84°E - 8" Jack Pine - 9.14' N46°W - 14" Red Pine - 18.26' N22°W - 14" Red Pine - 14.44' S01°28'E - 1" Iron rod - 55.64' Kelkeska County Peer Group accepted the	tions 30 and 31, T27 onument 12" below the	N-R8W and Sections 25 and 36, surface of the ground referred to in	T27N-R9W: Liber 3 Page 478 Grand Traverse County.
Ratified by Peer Group			OF MICHIGAN
P.A. 345 - 1990 Kalkaska Cou	nty		EUGENE D.
Chairman Andrews	me.		F* FARRIER *

Date

Signed by C= WIMU Surveyor's Michigan License No.\_

24594

3026913 Page: 1 of 1 e2/15/2001 10:28A REMON LB: 8 PG: 242 PROFESSIONAL SURVEYORS, JAN. 29, 1971 REVISED MAY 14,1975 REVISED JAN., 1993 NEVISED OCT., 1996