

SURVEY & REMONUMENTATION

FEB 14 1997

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970 KENT COUNTY REMONUMENTATION

For corners in

COMMISSION

Kent
(County)

Located in: Caledonia
Township

Corner Code #

1. Public Land Survey

T _____ R _____
T _____ R _____
T _____ R _____
T _____ R _____

2. Property Controlling
in Section

S 12 T 5N R 10W

East Witness

3. Miscellaneous

S _____ T _____ R _____

Monument

Property in Sec.

S _____ T _____ R _____

113.39' East of K-4

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

I, Randy Kolehouse, in a field survey on May 6 19 96, do hereby certify that under requirements of P.A. 74 Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

K-4C	1831	G.L.O. Notes	Mullett	Corner Falls in Lake - Set Temporary Point
	N/A	Notes	All Points	Iron Pipe
	1993	L.C.R.C. #6725	T. Chettleburgh	Fnd. Iron Bar / Set K.C. Monument
	1993	L.C.R.C. #8137	K. Breitels	K.C. Monument

P.A. 345 1990 KENT COUNTY

PEER APPROVED 8/22/96

CHAIRMAN Randy Kolehouse

This corner was originally approved by the Kent County Remonumentation Peer Group and monumented by T. Chettleburgh on 1/14/93 and was recorded per L.C.R.C. #6725.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

K-4C Found a Standard Kent County Monument 3' East of the East shore of Kettle Lake per L.C.R.C.'s #6725 and #8137 as set by T. Chettleburgh in place of an iron bar he found at the N 1/8 Corner, SW 1/4, Section 12, which checked the notes All Points.

L.C.R.C. #6725

Nail/Tag W side 16" Oak N 14° E 43.15'
Nail/Tag N side 11" Oak S 84° E 12.28'
Nail/Tag NE side 12" Oak S 49° E 10.73'
Nail/Tag SW side 13" Oak S 47° E 28.61'
Shore Kettle Lake West 3.00'

L.C.R.C. #8137

Nail/tag W. side 16" Oak N 14° E 43.19'
Nail/tag N. side 11" Oak S 84° E 12.33'
Nail/tag NE side 12" Oak S 49° E 10.78'
Nail/tag SW side 13" Oak S 47° E 28.66'
Shore Kettle Lake - West 3'

The selected location is accepted by me and is generally accepted by professional surveyors as the best available evidence of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

K-4C Standard Kent County Monument

Nail & K.C. remon. tag on W side 16" Oak N 14° E 43.19'
Nail & K.C. remon. tag on N side 11" Oak S 84° E 12.33'
Nail & K.C. remon. tag on NE side 12" Oak S 49° E 10.78'
Nail & K.C. remon. tag on SW side 13" Oak S 47° E 28.66'
East Shore Kettle Lake West 3' M/L

Signed by Randy J. Kolehouse

EARTH TECH

Date 10/8/96

Surveyor's Michigan License No. 25854

