

\$7.00 SEP 18 1995

\$2.00 COMMISSION

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970  
KENT COUNTY REMONUMENTATION

For corners in

Kent  
(County)

Located in:

Corner Code #

1. Public Land Survey T 5N R 12W A-6  
T R  
T R  
T R
2. Property Controlling S T R  
in Section S T R
3. Miscellaneous S T R  
Property in Sec. S T R

4. Lot No. , Recorded Plat
5. Private Claims

STATE OF MICHIGAN  
COUNTY OF KENT  
RECEIVED FOR RECORD  
95 AUG 28 AM 10:46  
REG. OF DEEDS  
8549

Register of Deeds Stamp & File Number

I, Randy Kolehose, in a field survey on March 13 19 95, do hereby certify that under requirements of P.A. 74 Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

A-6 This corner was not originally set by the G.L.O.

1937	Survey Records	K.C. Surveyor	Leaded Stone
1976	L.C.R.C. #1003	Medema, Van Kooten & Assoc.	1/2" Iron
1981	L.C.R.C. #1553	Nederveld & Jonker	End 1/2" Iron Rod/Set K.C. Monument
1988	L.C.R.C. #4628	Olson, Meyers & May	K.C. Monument
1990	L.C.R.C. #5704	J. Bueche	K.C. Monument

P.A. 345 1990 KENT COUNTY

PEER APPROVED 5/29/95

CHAIRMAN Randy Kolehose

This corner was originally approved by the Kent County Remonumentation Peer Group and monumented by Nederveld & Jonker on 1/27/81 and was recorded per L.C.R.C. #1553.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

A-6 Found standard Kent County Monument on the Town line 2' M/L East of the C/L of Kenowa Avenue running N-S per above L.C.R.C. as set by Nederveld & Jonker in place of a 1/2" round iron they found which checked L.C.R.C. #1003.

L.C.R.C. #1553

L.C.R.C. #5704

NW corner hse. SE 80.0'	NW cor. hse. S 40° E 80.00'
Nail & remon. tag on W side 10" Maple SSE 71.66'	Nail & remon. tag on W side 10" Maple S 10° E 71.66'
Nail & remon. tag on SE side 34" Maple NNE 120.75'	Nail & remon. tag S side 14" Elm S 85° E 21.86'
Ottawa County corner S 142.3'	Iron East 33'
Iron E 33'	Capped Iron S 142.12'

The selected location is accepted by me and is generally accepted by professional surveyors as the best available evidence of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

A-6 Standard Kent County Monument on the Town Line

NW cor. hse. S 40° E 79.92'  
Nail & K.C. remon. tag on W side 16" Maple S 10° E 71.68'  
Square spike SE side 38" Maple N 20° E 120.72'  
Nail & K.C. remon. tag on S side 24" Elm S 85° E 21.85'  
SE cor. barn fndn. N 20° W 200.20'  
Iron East 33.0'  
Capped iron (illegible) South 142.12'

Signed by Randy J. Kolehose

Date

8/21/95

EARTH TECH

Surveyor's Michigan License No. 25854

