

SURVEY &  
REMONUMENTATION  
\$7.00  
\$2.00 SEP 18 1995

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970  
KENT COUNTY REMONUMENTATION

For corners in

Kent (County)	Located in:	Corner Code #
1. Public Land Survey	T <u>5N</u> R <u>12W</u>	<u>A-10</u>
	T _____ R _____	_____
	T _____ R _____	_____
	T _____ R _____	_____
2. Property Controlling in Section	S _____ T _____ R _____	_____
	S _____ T _____ R _____	_____
3. Miscellaneous Property in Sec.	S _____ T _____ R _____	_____
	S _____ T _____ R _____	_____

STATE OF MICHIGAN  
COUNTY OF KENT  
RECEIVED FOR RECORD  
95 AUG 28 AM 10:47  
REG. OF DEEDS  
8553

Register of Deeds Stamp & File Number

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_  
5. Private Claims \_\_\_\_\_

I, Randy Kolehouse, in a field survey on March 13 19 95,  
do hereby certify that under requirements of P.A. 74 Michigan P.A. of 1970, the corner points  
mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required  
in the current manual of survey instructions of the United States Department of the Interior, Bureau of  
Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3,  
4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a  
Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered,  
found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded  
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

A-10 This corner was not originally set by the G.L.O.

1940	Wit. Map	K.C. Surveyor	Monument
1973	L.C.R.C. #366	Clapp	1" Iron Pipe
1981	L.C.R.C. #1556	Nederveld & Jonker	Fnd. 1" Iron/Set K.C. Monument
1988	L.C.R.C. #4632	Olson, Meyers & May	K.C. Monument

P.A. 345 1990 KENT COUNTY

PEER APPROVED 5/25/95

CHAIRMAN Randy Kolehouse

This corner was originally approved by the Kent County Remonumentation Peer Group and monumented by Nederveld &  
Jonker on 1/21/81 and was recorded per L.C.R.C. #1556.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

A-10 Found standard Kent County Monument on the West edge of Kenowa Avenue (gravel) running N-S per L.C.R.C.'s #1556 and  
#4632 as set by Nederveld & Jonker in place of a 1" iron pipe over a plat monument they found which checked L.C.R.C. #366  
and also one witness from K.C. Surveyor's records.

L.C.R.C. #1556

L.C.R.C. #4632

Nail & remon. tag on NE side 34" maple NW 25.27'  
Nail & remon. tag on NW side tw 10" maple SW 33.56'  
Nail & remon. tag on S side P. pole E 163.7'  
Ottawa Co. corner S 69.15'

Nail & Remon tag on NE sde 36" Maple N 40° W 25.18'  
Nail & Remon tag on NW sde twin 12" Maple S 30° W 33.47'  
Ottawa County cor S 69.15'

The selected location is accepted by me and is generally accepted by professional surveyors as the best available evidence  
of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

A-10 Standard Kent County Monument

Nail & K.C. remon. tag on NW side Twin 12" Maple S 30° W 33.47'  
Nail & K.C. remon. tag on NE side 36" Maple N 40° W 25.18'  
Nail & K.C. remon. tag on S side P. pole S 80° E 163.93'  
Nail & K.C. remon. tag on W side 10" tree S 25° E 48.83'  
Nail & K.C. remon. tag on S side wood corner fence post S 90° E 39.65'  
Ottawa County corner South 69.15'

Signed by Randy J. Kolehouse Date 8/21/95  
EARTH TECH

Surveyor's Michigan License No. 25854

