

~~\$7.00~~
~~\$2.00~~
SURVEY &
REMONUMENTATION

SEP 18 1995

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970
KENT COUNTY REMONUMENTATION

For corners in

Kent
(County)

Located in:

Corner Code #

- | | | | |
|------------------------------------|------|-------|-----|
| 1. Public Land Survey | T 5N | R 12W | B-1 |
| | T | R | |
| | T | R | |
| | T | R | |
| 2. Property Controlling in Section | S | T | R |
| | S | T | R |
| 3. Miscellaneous | S | T | R |
| Property in Sec. | S | T | R |

STATE OF MICHIGAN
STATE BOARD OF LAND SURVEYORS
RECEIVED FOR RECORD
95 AUG 28 AM 10:47
95 AUG 28 AM 10:47
8557
Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, Randy Kolehouse, in a field survey on June 20 19 94, do hereby certify that under requirements of P.A. 74 Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

B-1	1831	G.L.O. Notes	L. Lyon
	??	Wit Map	KC Surveyor
	1982	L.C.R.C. 2936	Exxel Eng.
	1982	L.C.R.C. 3181	Jonker

Set Post P.A. 345 1990 KENT COUNTY
3/4" Iron PEER APPROVED 8/24/95
3/4" Iron CHAIRMAN
Found 3/4" Iron/Set K.C. Mon.

A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1						
3												
4	7	6	5	4	3	2	1					
5												
6	18	17	16	15	14	13						
7												
8	19	20	21	22	23	24						
9												
10	30	29	28	27	26	25						
11												
12	31	32	33	34	35	36						
13												

This corner was originally approved by the Kent County Remonumentation Peer Group and monumented by Jonker Land Surveys on 11/19/82 and was recorded per L.C.R.C. #3181.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

B-1 Found KC Monument per L.C.R.C. 3181 as set by Rub Jonker in place of a 3/4" iron he found using KC Surveyor Records and L.C.R.C. #2936.

L.C.R.C. #3181

Remon. tag on N side 10" Ash S 50° W 7.55'
Remon. tag on E side 14" Ash N 45° W 9.15'
Remon. tag on NW side 40" Oak N 10° E 57.15'
Remon. tag on N side 8" Oak N 65° E 36.08'
In N-S fence and tree line

The selected location is accepted by me and is generally accepted by professional surveyors as the best available evidence of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

B-1 Standard Kent County Monument

Nail & K.C. remon. tag on N side 10" Ash S 50° W 7.55'
Nail & K.C. remon. tag on E side 14" Ash N 45° W 9.15'
Nail & K.C. remon. tag on NW side 40" Oak N 10° E 57.15'
Nail & K.C. remon. tag on N side 8" Oak N 65° E 36.08'
In N-S fence and tree line

Signed by Randy J. Kolehouse
EARTH TECH

Date 8/21/95

Surveyor's Michigan License No. 25854

