

SURVEYOR
REMONUMENTATION
\$7.00
\$2.00 SEP 18 1995

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970
KENT COUNTY REMONUMENTATION

For corners in

Kent
(County)

Located in:

Corner Code #

- | | | | | | |
|---------------------------------------|---|----|---|-----|-----|
| 1. Public Land Survey | T | 5N | R | 12W | B-9 |
| | T | | R | | |
| | T | | R | | |
| | T | | R | | |
| 2. Property Controlling
in Section | S | | T | | R |
| | S | | T | | R |
| 3. Miscellaneous
Property in Sec. | S | | T | | R |
| | S | | T | | R |

STATE OF MICHIGAN
COUNTY OF KENT
RECEIVED FOR RECORD
95 AUG 28 AM 10:48
8561
Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, Randy Kolehhouse, in a field survey on March 14 19 95,
do hereby certify that under requirements of P.A. 74 Michigan P.A. of 1970, the corner points
mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required
in the current manual of survey instructions of the United States Department of the interior, Bureau of
Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3,
4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a
Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered,
found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

B-9	1831	G.L.O. Notes	Mullett	Set Post
	1953	wit. Map	K.C. Surveyor	Axle Shaft
	1981	L.C.R.C. #1560	Nederveld & Jonker	Fnd. Axle Shaft/Set K.C. Monument
	1981	L.C.R.C. #2070	Nederveld & Jonker	Axle Shaft
	1988	L.C.R.C. #4624	Olson, Meyers & May	K.C. Monument

P.A. 345 1990 KENT COUNTY

PEER APPROVED

CHAIRMAN Randy Kolehhouse

This corner was originally approved by the Kent County Remonumentation Peer Group and monumented by Nederveld & Jonker on 1/12/81 and was recorded per L.C.R.C. #1560.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

- B-9 Found standard Kent County Monument on the C/L of 92nd Street running E-W on line of tree row running North per
L.C.R.C.'s #1560 and #4624 as set by Nederveld & Jonker in place of a 30" axle shaft found which checked the K.C.
Surveyor records.

L.C.R.C. #1560

L.C.R.C. #2070

Nail & Remon. tag on NE side P. pole NW 48.53'
Nail & Remon. tag on NE side 20" W Cherry ESE 75.48'
Nail & Remon. tag on W side P. pole S 54.68'

Nail & Remon. tag on NE sde P pole N 50 W 48.53'
Nail & Remon. tag on NE sde 22" W cherry S 65 E 75.48'
Nail & Remon. tag on W sde P pole S 0 E 54.68'

The selected location is accepted by me and is generally accepted by professional surveyors as the best available evidence
of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

- B-9 Standard Kent County Monument

Nail & K.C. remon. tag on NE side P. pole N 50° W 48.53'
Nail & K.C. remon. tag on W side P. pole S 0° E 54.68'
Nail & K.C. remon. tag on NE side 24" W. Cherry S 65° E 75.48'
Nail & K.C. remon. tag on W side 12" W. Cherry S 15° E 30.76'

Signed by Randy J Kolehhouse Date 8/21/95

EARTH TECH

Surveyor's Michigan License No. 25854

