



## LAND CORNER RECORDATION CERTIFICATE

Kent   Located in:   Corner Code #   DT   CEV	<b>3</b> 0
1. Public Land Survey  T 5N R 12W B-10  T R  T R  2. Property Controlling S T R  3. Miscellaneous S T R  Property in Sec. S T R  4. Lot No. Recorded Plat  5. Private Claims  1, Randy Kolehouse in a field survey on October 10  19 95  4. Lot No. S T R  10 Register of Deeds Stamp & File No  Register of Deeds Stamp & File No  1, Randy Kolehouse in a field survey on October 10  19 95  10 A B C D F R N I R  10 A B C D F R N I R  10 A B C D F R N I R  10 A B C D F R N I R  10 A B C D F R N I R  11 A B C D F R N I R  12 A B C D F R N I R  13 A B C D F R N I R  14 A B C D F R N I R  15 A B C D F R N I R  16 A B C D F R N I R  17 A B C D F R N I R  18 A B C D F R N I R  19 A B C D F R N I R  10 A B C D F R N I R  10 A B C D F R N I R  10 A B C D F R N I R  10 A B C D F R N I R  10 A B C D F R N I R  10 A B C D F R N I R  10 A B C D F R N I R  10 A B C D F R N I R  10 A B C D F R N I R  10 A B C D F R N I R  10 A B C D F R N I R  10 A B C D F R N I R  10 A B C D F R N I R  10 A B C D F R N I R  10 A B C D F R N I R  10 A B C D F R N I R  11 A B C D F R N I R  12 A B C D F R N I R  13 A B C D F R N I R  14 A B C D F R N I R  15 A B C D F R N I R  16 A B C D F R N I R  17 A B C D F R N I R  18 A B C D F R N I R  19 A B C D F R N I R  10 A B C D F R  10 A B C D	
2. Property Controlling in Section S. T. R. S. S. T. R. S. S. T. R. S. S. T. R. S. S. T. R. S. S. T. R. S. S. T. R. S. T	
3. Miscellaneous S T R R Register of Deeds Stamp & File No.  4. Lot No. , Recorded Plat  5. Private Claims	
i, Randy Kolehouse, in a field survey on October 10 19 95, do hereby certify that under requirements of P.A. 74 Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law, established, re-established, monumented, re-monumented, recovered, found as expressed below:  NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.  A. Description of original monument and accessories and/or subsequent restoration:  B-10 This corner was not originally set by the G.L.O.  Wit. Map K.C. Surveyor Leaded Stone (not found)  P.A. 345 1990 KENT COUNT	Number
I, Randy Kolehouse, in a field survey on October 10 19 95, do hereby certify that under requirements of P.A. 74 Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:  NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.  A. Description of original monument and accessories and/or subsequent restoration:  B-10 This corner was not originally set by the G.L.O.  Wit. Map K.C. Surveyor Leaded Stone (not found)  P.A. 345 1990 KENT COUNT	
Wit. Map K.C. Surveyor Leaded Stone (not found)  P.A. 345 1990 KENT COUNT	11 12 12 13 14 13 13 14 13 14 13 15 15 15 15 15 15 15 15 15 15 15 15 15
P.A. 345 1990 KENT COUNT	
CHAIRMAN CHA	108

- iption of corner evidence found and/or method applied in restoring or reestablishing corner:
- B-10 Set Kent County Monument at intersection of 1/4 lines 6.5' North of intersection of broken down fence lines running South and East.

Description of monument for corner and accessories established to perpetuate locating the position of the corner B-10 Set a Standard 4" x 30" Kent County Monument. RANDY J.

Nail & K.C. remon. tag in W face 12" Ash S 15° E 8.83' Nail & K.C. remon. tag in W face 14" W. Sherry S 5° W 42.48' Nail & K.C. remon. tag in SE face 8" W. Cherry S 40° W 50.571

25854

Nail & K.C. remon. tag in N face 4" Ash S 75° W 17.44'

Signed by

Surveyor's Michigan License No. \_\_\_

NED LAND SUR

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971 REVISED MAY 14, 1975 REVISED JAN.. 1983

KOLEHOUSE

SURVEYOR

25854