

SURVEY & RECONSTRUCTION  
\$7.00  
\$2.00

JAN 23 1996

Seq 2

COMMISSION

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970  
KENT COUNTY REMONUMENTATION

For corners in

Kent  
(County)

Located in:

Corner Code #

1. Public Land Survey

T 5N R 12W

B-12

T

R

T

R

T

R

2. Property Controlling  
in Section

S

T

R

S

T

R

3. Miscellaneous

S

T

R

Property in Sec.

S

T

R

REG. OF DEEDS

8882

95 DEC 28 PM 2:18

STATE OF MICHIGAN  
COUNTY OF KENT  
RECEIVED FOR RECORD

Register of Deeds Stamp & File Number

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_

5. Private Claims \_\_\_\_\_

I, Randy Kolehhouse, in a field survey on March 14 19 95,  
do hereby certify that under requirements of P.A. 74 Michigan P.A. of 1970, the corner points  
mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required  
in the current manual of survey instructions of the United States Department of the interior, Bureau of  
Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3,  
4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a  
Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered,  
found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded  
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

B-12 This corner was not originally set by the G.L.O.

1994

L.C.R.C. #7845

Jonker Land Surveys

Set K.C. Monument at Int. of 1/4 Lines

P.A. 345 1990 KENT COUNTY

PEER APPROVED 8/24/99

CHAIRMAN Randy Kolehhouse

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

B-12 Found K.C. Monument 2.5' South of the C/L of 104th Street per L.C.R.C. #7845. Monument is 0.1' North and 0.1' West of  
Intersection of 1/4 lines. Accepted Kent County Monument as Center Section.

L.C.R.C. #7845

Nail E. side P. pole Az. 350° 90.25'

Spk. W. side 9" Elm Az. 175° 35.6'

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

B-12 Standard Kent County Monument

Nail & K.C. remon. tag in W side 8" Maple S 5° E 35.59'

Nail & K.C. remon. tag in NE side 24" Maple S 45° E 84.84'

Nail & K.C. remon. tag in E side P. pole N 13° W 90.28'

Nail & K.C. remon. tag in N side 18" Maple S 88° W 144.73'

Signed by Randy J. Kolehhouse

EARTH TECH

Date

12/22/95

Surveyor's Michigan License No. 25854

