

\$7.00
\$2.00

SEP 13 1995

COMMISSION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970
KENT COUNTY REMONUMENTATION

For corners in

Kent
(County)

Located in:

Corner Code #

- | | | | | | |
|------------------------------------|---|----|---|-----|-----|
| 1. Public Land Survey | T | 5N | R | 12W | C-8 |
| | T | | R | | |
| | T | | R | | |
| | T | | R | | |
| 2. Property Controlling in Section | S | | T | | |
| | S | | T | | |
| 3. Miscellaneous Property in Sec. | S | | T | | |
| | S | | T | | |

REC. OF DEEDS

8571

Register of Deeds Stamp & File Number

STATE OF MICHIGAN
COUNTY OF KENT
RECEIVED FOR RECORD
95 AUG 28 AM 10:48

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, Randy Kolehouse, in a field survey on March 14 19 95, do hereby certify that under requirements of P.A. 74 Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

C-8	1831	G.L.O. Notes	Mullett	Set Post
	1944	Wit. Map	K.C. Surveyor	Iron on Stone
	1954	Wit. Map	K.C. Surveyor	Iron in Monument Box
	1973	L.C.R.C. #638	Exxel Engineering	Iron in Monument Box
	1981	L.C.R.C. #1570	Nederveld & Jonker	Iron in Monument Box/Set K.C. Monument
	1988	L.C.R.C. #4641	Olson, Meyers & May	K.C. Monument

This corner was originally approved by the Kent County Remonumentation Peer Group and monumented by Nederveld & Jonker on 1/5/81 and was recorded per L.C.R.C. #1570.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

C-8 Found standard Kent County Monument in a monument box per L.C.R.C.'s #1570 and #4641 at the C/L intersection of Wilson Avenue running N-S and 88th Street running West as set by Nederveld & Jonker in place of a 1/2" iron in a monument box they found which checked L.C.R.C. #638.

L.C.R.C. #1570

Face conc. R.O.W. marker WSW 128.97'
"X" on curb NW 36.00'

L.C.R.C. #4641

Nail & Remon tag in SW sde 12" Mulberry S 50° E 43.77'
Nail & Remon tag in W sde twin 6" Mulberry N 40° E 60.46'
Face conc R.O.W. marker S 80° W 128.97'
"X" on curb N 45° W 36.00'

The selected location is accepted by me and is generally accepted by professional surveyors as the best available evidence of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

C-8 Standard Kent County Monument in a Monument Box

Nail & K.C. remon. tag on SW side 12" Mulberry S 50° E 43.77'
Nail & K.C. remon. tag on W side Twin 6" Mulberry N 40° E 61.48'
"X" on conc. curb N 45° W 36.00'
Face conc. R.O.W. marker S 80° W 128.97'
Nail & K.C. remon. tag on N side P. pole S 87° E 24.14'

Signed by Randy J. Kolehouse Date 8/21/95

EARTH TECH

Surveyor's Michigan License No. 25854

