

\$7.00
\$2.00

SEP 18 1995

COMMISSION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970
KENT COUNTY REMONUMENTATION

For corners in

Kent
(County)

Located in:

Corner Code #

- | | | | |
|---------------------------------------|------|-------|------|
| 1. Public Land Survey | T 5N | R 12W | C-11 |
| | T | R | |
| | T | R | |
| | T | R | |
| 2. Property Controlling
in Section | S | T | R |
| | S | T | R |
| 3. Miscellaneous
Property in Sec. | S | T | R |
| | S | T | R |

REG. OF DEEDS

95 AUG 28 AM 10:48

STATE OF MICHIGAN
COUNTY OF KENT
RECEIVED FOR RECORD

8574

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, Randy Kolehose, in a field survey on March 14 19 95,
do hereby certify that under requirements of P.A. 74 Michigan P.A. of 1970, the corner points
mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required
in the current manual of survey instructions of the United States Department of the Interior, Bureau of
Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3,
4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a
Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered,
found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

C-11	1831	G.L.O. Notes	Mullett	Set Post
	1940	Wit. Map	K.C. Surveyor	Monument
	1959	Wit. Map	K.C. Surveyor	Monument Box
	1973	L.C.R.C. #601	Medema, Van Kooten & Assoc.	1/2" Iron in Monument Box
	1981	L.C.R.C. #1573	Nederveld & Jonker	Fnd. 1/2" Iron in Mon. Box/Set K.C. Monument
	1988	L.C.R.C. #4642	Olson, Meyers & May	K.C. Monument
	1990	L.C.R.C. #5705	J. Bueche	K.C. Monument

P.A. 345 1990 KENT COUNTY

PEER APPROVED 5/25/95

CHAIRMAN Randy Kolehose

This corner was originally approved by the Kent County Remonumentation Peer Group and monumented by Nederveld & Jonker on 1/5/81 and was recorded per L.C.R.C. #1573.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

C-11 Found standard Kent County Monument in a monument box 1' M/L South of the C/L of 100th Street running E-W and 2' M/L
East of the C/L of Wilson Avenue running N-S per L.C.R.C.'s #1573, #4642 and #5705 as set by Nederveld & Jonker in place
of a 1/2" iron in monument box they found which checked L.C.R.C. #601 and the K.C. Surveyor records from 1959 and 1940.

L.C.R.C. #4642

L.C.R.C. #5705

K.C.R.C. Remon tag & nail on E sde 26" twin Ash S 15° E 95.4'
K.C.R.C. Remon tag & nail on E sde fence cor post S 70° W 60.9'
K.C.R.C. Remon tag & nail on NE sde P & L pole N 40° W 47.4'

Nail remon. tag & nail on E side 26" Twin Ash S 15° E 95.40'
Nail remon. tag & nail on E side fence cor. post S 70° W 61.02'
Nail remon tag & nail on NE side P & L pole N 40° W 47.40'
"X" cut on curb S 50° E 36.22'

The selected location is accepted by me and is generally accepted by professional surveyors as the best available evidence
of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

C-11 Standard Kent County Monument in a Monument Box

"X" on conc. curb S 50° E 36.22'
Nail & K.C. remon. tag on NE P. & L. pole N 40° W 48.47'
Nail & K.C. remon. tag on E side fence post S 70° W 61.02'
Nail & K.C. remon. tag on E side 26" Twin Ash S 15° W 95.40'
Nail & K.C. remon. tag on W side 28" Ash S 15° E 97.28'

Signed by Randy Kolehose
EARTH TECH

Date

8/21/95

Surveyor's Michigan License No. 25854

