

# SURVEY & REMONUMENTATION

SEP 13 1995

COMMISSION

## LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970 KENT COUNTY REMONUMENTATION

For corners in

Kent  
(County)

Located in:

Corner Code #

- |                                    |               |               |               |
|------------------------------------|---------------|---------------|---------------|
| 1. Public Land Survey              | T <u>5N</u>   | R <u>12W</u>  | <u>D-3</u>    |
|                                    | T <u>    </u> | R <u>    </u> | <u>    </u>   |
|                                    | T <u>    </u> | R <u>    </u> | <u>    </u>   |
|                                    | T <u>    </u> | R <u>    </u> | <u>    </u>   |
| 2. Property Controlling in Section | S <u>    </u> | T <u>    </u> | R <u>    </u> |
|                                    | S <u>    </u> | T <u>    </u> | R <u>    </u> |
| 3. Miscellaneous Property in Sec.  | S <u>    </u> | T <u>    </u> | R <u>    </u> |
|                                    | S <u>    </u> | T <u>    </u> | R <u>    </u> |

REG. OF DEEDS

*Handwritten signature*

95 AUG 28 AM 10:49

STATE OF MICHIGAN  
COUNTY OF KENT  
RECEIVED FOR RECORD

8578

Register of Deeds Stamp & File Number

4. Lot No.                     , Recorded Plat
5. Private Claims

I, Randy Kolehhouse, in a field survey on March 15 19 95, do hereby certify that under requirements of P.A. 74 Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

### A. Description of original monument and accessories and/or subsequent restoration:

D-3	1831	G.L.O. Notes	Mullett	Set Post	P.A. 345 1990 KENT COUNTY
	1940	Wit. Map	K.C. Surveyor	Stone	PEER APPROVED <u>8/24/95</u>
	1956	Wit. Map	K.C. Surveyor	Iron in Mon. Box	CHAIRMAN <u>Handwritten signature</u>
	1972	L.C.R.C. #151	Medema, Van Kooten & Assoc.	Iron in Mon. Box	
	1972	L.C.R.C. #167	Medema, Van Kooten & Assoc.	Iron in Mon. Box	
	1972	L.C.R.C. #195	Williams & Works	Iron in Mon. Box	
	1972	L.C.R.C. #249	Williams & Works	Iron in Mon. Box	
	1981	L.C.R.C. #1645	Nederveld & Jonker	End. Iron in Mon. Box over Stone/Set K.C. Monument	
	1988	L.C.R.C. #4659	Olson, Meyers & May	K.C. Monument	

This corner was originally approved by the Kent County Remonumentation Peer Group and monumented by Nederveld & Jonker on 2/16/81 and was recorded per L.C.R.C. #1645.

### B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

- D-3 Found standard Kent County Monument in a monument box at the C/L intersection of Homrich Avenue running N-S and 68th Street running E-W per L.C.R.C. #1645 and 4659 as set by Nederveld & Jonker in place of a 1" iron over a stone in a monument box they found which checked L.C.R.C. #151 and the K.C. Surveyor records.

L.C.R.C. #1645

L.C.R.C. #4659

Nail & Remon. tag on W side 20" Cedar NE 51.90' - N45°E  
Nail & Remon. tag on W side P. pole NNE 117.93' - N15°E  
NW cor. hse found SE 133.76' - S30°E  
NE cor. hse found SW 118.0' - S45°W  
SE cor. former school house NW 95.05' - N35°W

Nail & Remon tag on W side 22" Cedar N 45° E 51.90'  
Nail & Remon tag on W side P pole N 15° E 117.93'  
NW cor hse fndn S 30° E 133.76'  
NE cor hse fndn S 45° W 118.0'  
SE cor former school hse N 35° W 95.05'

The selected location is accepted by me and is generally accepted by professional surveyors as the best available evidence of the position of the original corner.

### C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

#### D-3 Standard Kent County Monument

Nail & K.C. remon. tag on W side 22" Cedar N 45° E 51.90'  
Nail & K.C. remon. tag on P. pole N 15° E 118.00'  
NW cor. hse. fndn. S 30° E 133.76'  
NE cor. hse. fndn. S 45° W 118.00'  
SE cor. former school hse. N 35° W 94.88'

Signed by Randy J Kolehhouse

Date 8/21/95

EARTH TECH

Surveyor's Michigan License No. 25854

