

JAN 23 1996

COMMISSION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970
KENT COUNTY REMONUMENTATION

For corners in

| Kent (County) | Located in: | Corner Code # |
|---------------------------------------|--------------------------|---------------|
| 1. Public Land Survey | T <u>5N</u> R <u>12W</u> | <u>D-4</u> |
| | T _____ R _____ | |
| | T _____ R _____ | |
| | T _____ R _____ | |
| 2. Property Controlling in Section | S _____ T _____ R _____ | <u>Seg. 1</u> |
| | S _____ T _____ R _____ | |
| 3. Miscellaneous Property in Sec. | S _____ T _____ R _____ | |
| | S _____ T _____ R _____ | |

STATE OF MICHIGAN
COUNTY OF KENT
RECEIVED FOR RECORD
95 OCT 31 AM 9:00
REG. OF DEEDS
8732
Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, Randy Kolehhouse, in a field survey on March 15 19 95, do hereby certify that under requirements of P.A. 74 Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

| | | | | |
|-----|-----------|--------------|-----------------------------|---|
| D-4 | 1912 | Survey Notes | Williams & Works | Found & Accepted Leaded Stone |
| | 1957-1959 | Survey Notes | Williams & Works | Set RR Spike at Int. of 1/4 Lines |
| | 1961-1965 | Survey Notes | Williams & Works | Set "T" Iron per Wit. for RR Spike Above |
| | 1972 | L.C.R.C. #51 | Medema, Van Kooten & Assoc. | Found "T" Iron within 1" of True Int. of 1/4 Lines - Accepted |

P.A. 345 1990 KENT COUNTY
PEER APPROVED 8/24/95
CHAIRMAN Harry Thibault

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

D-4 Found "T" iron 5.0' East of C/L of Homerich Avenue per L.C.R.C. #151 as accepted by MVK which they found to be within 1' of true 1/4 line intersection. "T" iron is 1.1' South and 0.10' East of the intersection of 1/4 lines. Measurements E-W & N check record measurements from Williams & Works & Jonker Land Surveys.

L.C.R.C. #151

SE cor. hse. W-SW 108.25'
NE cor. garage NW 147.03'
SW cor. garage NE 94.08'

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

D-4 Replaced "T" iron with a standard 4" x 30" Kent County Monument

Nail & K.C. remon. tag in W side 12" Ash S 12° E 81.44'
Nail & K.C. remon. tag in S side P. pole N 60° W 38.40'
SE corner hse. fndn. N 70° W 108.25'
NE corner garage fndn. N 42° W 147.15'
SW corner garage fndn. N 63° E 93.87'

Signed by Randy J. Kolehhouse
EARTH TECH

Date 10/25/95

Surveyor's Michigan License No. 25854

