

JAN 23 1996

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970
KENT COUNTY REMONUMENTATION

For corners in COMMISSION

Kent	Located in:	Corner Code #
(County)		
1. Public Land Survey	T 5N R 12W	D-6
	T R	
	T R	
	T R	
2. Property Controlling	S T R	Seg 1
in Section	S T R	
3. Miscellaneous	S T R	
Property in Sec.	S T R	

STATE OF MICHIGAN
COUNTY OF KENT
RECEIVED FOR RECORD
95 OCT 31 AM 9:00
REG. OF DEEDS
8733

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, Randy Kolehouse, in a field survey on March 15 19 95, do hereby certify that under requirements of P.A. 74 Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

D-6	1944	Wit. Map	K.C. Surveyor	2" Pipe
	1955-1966	Survey Notes	Williams & Works	Set PK per Wit. Map for Center Section
	1975	L.C.R.C. #910	Exxel Engineering	Found 1/2" Iron

P.A. 345 1990 KENT COUNTY

PEER APPROVED 8/24/95

CHAIRMAN Harry Huber

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

D-6 Found a 1" iron pipe in the approximate C/L of Homerich Avenue running N-S per L.C.R.C. #910. Iron is 0.1 South and 0.7 East of intersection of 1/4 lines. Checks Jonker Land Surveys' measurements West and South. Accepted 1" iron as Center Section.

L.C.R.C. #910

Nail in sde P. Pole East 53.42'
Nail in sde T. Pole West 23.76'
SE cor garage NW 80.37'
C/L 10" Walnut East 42.1'

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

D-6 Standard Kent County Monument

Nail & K.C. remon. tag in N side P. pole S 88° E 53.42'
Nail & K.C. remon. tag in S side T. pole N 85° W 23.89'
SE cor. garage N 65° W 80.50'
C/L 10" Walnut N 90° E 42.1'
Set "X" in N end conc. culvert S 20° W 57.47'
NE cor. bse. fndn. N 30° W 123.16'

Signed by Randy J. Kolehouse Date 10/25/95

EARTH TECH

Surveyor's Michigan License No. 25854

