

\$7.00  
\$2.00

SEP 13 1995

COMMISSION

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970  
KENT COUNTY REMONUMENTATION

For corners in

Kent  
(County)

Located in:

Corner Code #

- |                                       |             |              |            |
|---------------------------------------|-------------|--------------|------------|
| 1. Public Land Survey                 | T <u>5N</u> | R <u>12W</u> | <u>E-4</u> |
|                                       | T           | R            |            |
|                                       | T           | R            |            |
|                                       | T           | R            |            |
| 2. Property Controlling<br>in Section | S T         | R            |            |
|                                       | S T         | R            |            |
| 3. Miscellaneous                      | S T         | R            |            |
| Property in Sec.                      | S T         | R            |            |

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_
5. Private Claims \_\_\_\_\_

REG. OF DEEDS

8587

Register of Deeds Stamp & File Number

95 AUG 28 AM 10:49

STATE OF MICHIGAN  
COUNTY OF KENT  
RECEIVED FOR RECORD

I, Randy Kolehouse, in a field survey on April 14 19 95, do hereby certify that under requirements of P.A. 74 Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

E-4	1831	G.L.O. Notes	Mullett	Set Post
		Wit. Map	K.C. Surveyor	R.R. Spike
	1972	L.C.R.C. #401	Spicer	"T" Iron
	1983	L.C.R.C. #3588	J. Bueche	Fnd. "T" Iron/Set K.C. Monument
	1988	L.C.R.C. #4656	Olson, Meyers & May	K.C. Monument

This corner was originally approved by the Kent County Remonumentation Peer Group and monumented by J. Bueche on 8/30/83 and was recorded per L.C.R.C. #3588.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

E-4 Found standard Kent County Monument 3' North of C/L of 72nd to East on C/L Ivanrest running N-S and on a tree row to the West, per L.C.R.C.'s #3588 and #4656, as set by J. Bueche in place of a "T" iron which checked L.C.R.C. #401.

L.C.R.C. #3588

L.C.R.C. #4656

Pk nail in East end conc. culvert S10°E 137.57'  
"X" cut West end conc. culvert N 20°W 65.93'  
"X" cut West end conc. culvert S10°W 138.31'  
C/L blacktop road East is South 3' ±  
on C/L blacktop road N - S

PK nail in E end conc culvt. S 10 E 137.57'  
"X" cut W end conc culvt. N 20 W 65.93'  
"X" cut W end conc culvt. S 10 W 138.31'  
on C/L bit rd N-S  
on tree rd - W

The selected location is accepted by me and is generally accepted by professional surveyors as the best available evidence of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

E-4 Standard Kent County Monument

P.K. nail in E end conc. culv. side S 10° E 137.57'  
"X" cut West end conc. culv. N 20° W 65.93'  
"X" cut West end conc. culv. S 10° W 138.31'  
NE cor. brick pillar on S side of driveway N 80° W 86.39'

Signed by Randy J. Kolehouse  
EARTH TECH

Date 8/21/95

Surveyor's Michigan License No. 25854

