

\$2.00
\$2.00

SEP 13 1995

COMMISSION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970
KENT COUNTY REMONUMENTATION

For corners in

Kent
(County)

Located in:

Corner Code #

1. Public Land Survey

T 5N R 12W E-6

2. Property Controlling
in Section

S T R

3. Miscellaneous
Property in Sec.

S T R

4. Lot No. , Recorded Plat

5. Private Claims

REC. OF DEEDS

8589

95 AUG 28 AM 10:49

STATE OF MICHIGAN
COUNTY OF KENT
RECEIVED FOR RECORD

Register of Deeds Stamp & File Number

I, Randy Kolehhouse, in a field survey on April 14 19 95,
do hereby certify that under requirements of P.A. 74 Michigan P.A. of 1970, the corner points
mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required
in the current manual of survey instructions of the United States Department of the interior, Bureau of
Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3,
4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a
Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered,
found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

E-6 1831 G.L.O. Notes Mullett
1966 Wit. Map K.C. Surveyor
1975 L.C.R.C. #835 Exxel Engineering
1981 L.C.R.C. #1644 Nederveld & Jonker
1988 L.C.R.C. #4646 Olson, Meyers & May

Set Post P.A. 345 1990 KENT COUNTY
Pointed Stone PEER APPROVED 5/29/95
3/4" Iron CHAIRMAN
Fnd. 3/4" Iron/Set K.C. Monument
K.C. Monument

This corner was originally approved by the Kent County Remonumentation Peer Group and monumented by Nederveld & Jonker on 2/12/81 and was recorded per L.C.R.C. #1644.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

E-6 Found standard Kent County Monument 2' East of fence line running N-S, per L.C.R.C.'s #1644 and 4646, as set by Nederveld & Jonker in place of a 3/4" iron which checked L.C.R.C. #835.

L.C.R.C. #1644

L.C.R.C. #4646

Nail & Remon. tag E side 26" Maple NNW 29.33' -N20°W
Nail & Remon. tag N side 10" Ash WNW 1.93' -N80° W

Nail & Remon. tag E sde 28" Maple N 20° W 29.33'
Nail & Remon tag N sde 12" Ash N 80° W 1.93'

The selected location is accepted by me and is generally accepted by professional surveyors as the best available evidence of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

E-6 Standard Kent County Monument

Nail & K.C. remon. tag on N side 12" Ash (stump) N 80° W 1.93'
Nail & K.C. remon. tag on E side 28" Maple N 20° W 29.33'
Nail & K.C. remon. tag on S face 10" Ash S 81° E 7.86'
Nail & K.C. remon. tag on W face 14" Ash S 18° W 56.02'
Nail & K.C. remon. tag on E face 6" Cherry N 10° E 14.93'



Signed by Randy J. Kolehhouse

Date 8/21/95

EARTH TECH

Surveyor's Michigan License No. 25854