

\$7.00  
\$2.00

SEP 18 1995

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970  
KENT COUNTY REMONUMENTATION

For corners in

COMMISSION

Kent (County)	Located in:	Corner Code #
1. Public Land Survey	T <u>5N</u> R <u>12W</u>	<u>E-7</u>
	T _____ R _____	_____
	T _____ R _____	_____
	T _____ R _____	_____
2. Property Controlling in Section	S _____ T _____ R _____	_____
	S _____ T _____ R _____	_____
3. Miscellaneous	S _____ T _____ R _____	_____
Property in Sec.	S _____ T _____ R _____	_____

STATE OF MICHIGAN  
COUNTY OF KENT  
RECEIVED FOR RECORD  
95 AUG 28 AM 10:50  
REG. OF DEEDS  
8590

Register of Deeds Stamp & File Number

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_  
5. Private Claims \_\_\_\_\_

I, Randy Kolehhouse, in a field survey on April 14 19 95,  
do hereby certify that under requirements of P.A. 74 Michigan P.A. of 1970, the corner points  
mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required  
in the current manual of survey instructions of the United States Department of the interior, Bureau of  
Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3,  
4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a  
Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered,  
found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded  
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

E-7	1831	G.L.O. Notes	Mullett	Set Post
	1944	Wit. Map	K.C. Surveyor	1" Iron
	1975	L.C.R.C. #835	Exxel Engineering	3/4" Iron in Monument Box
	1981	L.C.R.C. #1634	Nederveld & Jonker	Replaced 3/4" Iron in Mon. Box w/Std. K.C. Mon.
	1988	L.C.R.C. #4647	Olson, Meyers & May	K.C. Monument in Mon. Box

This corner was originally approved by the Kent County Remonumentation Peer Group and monumented by Nederveld & Jonker on 3/6/81 and was recorded per L.C.R.C. #1634.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

E-7 Found standard Kent County Monument in a monument box 0.5' South of C/L of 84th Street running E-W on tree row running  
N-S, per L.C.R.C.'s #1634 and #4647, as set by Nederveld & Jonker in place of a 3/4" iron in said monument box which  
checks L.C.R.C. #835.

L.C.R.C. #1634

Nail & Remon. tag on E side P. pole S0°W 28.11'  
Nail & Remon. tag on S side P. pole N65°W 103.88'  
NE corner house fnd. S40°E 122.12'  
Centerline B.T. N 0.5'

L.C.R.C. #4647

Nail & Remon tag E sde P pole S 0 W 28.11'  
Nail & Remon tag S sde P pole N 65 W 103.88'  
K.C. Remon tag & nail in W sde 28" Elm S 5 E 39.78'  
NW cor hse fndn S 25 E 105.43'  
NE cor hse fndn S 40 E 122.12'  
C.L.B.T. N .5'

The selected location is accepted by me and is generally accepted by professional surveyors as the best available evidence  
of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

E-7 Standard Kent County Monument

Nail & K.C. remon. tag on E side P. pole due South 28.11'  
Nail & K.C. remon. tag on S side P. pole N 65° W 103.88'  
NE cor. hse. fndn. S 40° E 122.12'  
Nail & K.C. remon. tag on W side 28" Elm S 5° E 39.78'  
NW cor. hse. fndn. S 25° E 105.43'

Signed by

Randy J. Kolehhouse  
EARTH TECH

Date

8/21/95

Surveyor's Michigan License No.

25854

