

\$7.00
 \$2.00 SEP 13 1995

LAND CORNER RECORDATION CERTIFICATE
 Filing Requirement of Act 74, Mich. P.A. 1970
 KENT COUNTY REMONUMENTATION

For corners in

Kent
 (County)

Located in:

Corner Code #

- | | | | | | |
|------------------------------------|---|----|---|-----|-----|
| 1. Public Land Survey | T | 5N | R | 12W | F-3 |
| | T | | R | | |
| | T | | R | | |
| | T | | R | | |
| 2. Property Controlling in Section | S | | T | | |
| | S | | T | | |
| 3. Miscellaneous | S | | T | | |
| Property in Sec. | S | | T | | |

REC. OF DEEDS

95 AUG 28 AM 10:50
 RECEIVED FOR RECORD
 STATE OF MICHIGAN
 COUNTY OF KENT

8598

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
 5. Private Claims _____

I, Randy Kolehose, in a field survey on April 13 19 95, do hereby certify that under requirements of P.A. 74 Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

F-3	1831	G.L.O. Notes	Mullett	Set Post
	1960	Wit. Map	K.C. Surveyor	Iron
	1972	L.C.R.C. #420	Medema, Van Kooten & Assoc.	Fnd. "T" Iron
	1981	L.C.R.C. #1540	Exxel Engineering	Fnd. "T" Iron/Set K.C. Monument
	1988	L.C.R.C. #4615	Olson, Meyers & May	K.C. Monument

P.A. 345 1900 KENT COUNTY

PEER APPROVED 5/29/95

CHAIRMAN

This corner was originally approved by the Kent County Remonumentation Peer Group and monumented by Exxel Engineering on 12/10/80 and was recorded per L.C.R.C. #1540.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

F-3 Found standard Kent County Monument \pm 80' W of C/L of Kent Trails running N-S and on a fence line running E-W and 30' West of a fence line running N-S. Per L.C.R.C.'s #1540 and #4615 as set by Exxel Engineering in place of a "T" iron they found which checked L.C.R.C. #420.

L.C.R.C. #1540

L.C.R.C. #4615

Nail & tag in W. sde 6" W. Cherry (2.5' above ground)

S10°E 19.63'

Nail & tag in S sde Twin 14" Wild Cherry (3' above ground)

N55°E 38.27'

Nail & tag in NE sde 6" Aspen (2.5' above ground)

N47°W 7.05'

New nail & tag in W sde 8" W. Cherry (2.5' above ground)

S 10 E 19.65'

Nail & K.C. Remon tag S sde twin 16" W. Cherry (3' above ground)

N 55 E 38.2'

Nail & K.C. Remon tag S sde of 12" Cherry S 65° E 53.58'

The selected location is accepted by me and is generally accepted by professional surveyors as the best available evidence of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

F-3 Standard Kent County Monument

Nail & K.C. remon. tag on W side 8" Cherry S 10° E 19.65'

Nail & K.C. remon. tag on S side Twin Cherry N 55° E 38.25'

Nail & K.C. remon. tag on NE side 8" Aspen N 47° W 7.05'

Nail & K.C. remon. tag on S side 12" Cherry S 65° E 53.71'

Signed by Randy J. Kolehose

EARTH TECH

Date

8/21/95

Surveyor's Michigan License No. 25854

