

\$20.00 SEP 1 5 1995
\$2.00 COMMISSION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970
KENT COUNTY REMONUMENTATION

For corners in

Kent
(County)

Located in:

Corner Code #

1. Public Land Survey

T 5N R 12W

H-1

2. Property Controlling
in Section

S T R

3. Miscellaneous
Property in Sec.

S T R

4. Lot No. , Recorded Plat

5. Private Claims

STATE OF MICHIGAN
COUNTY OF KENT
RECEIVED FOR RECORD
95 AUG 28 AM 10:52
REG. OF DEEDS
8617

Register of Deeds Stamp & File Number

I, Randy Kolehose, in a field survey on April 13 19 95,
do hereby certify that under requirements of P.A. 74 Michigan P.A. of 1970, the corner points
mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required
in the current manual of survey instructions of the United States Department of the Interior, Bureau of
Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3,
4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a
Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered,
found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

H-1

1965

Wit. Map

K.C. Surveyor

Leaded Stone Monument

1983

L.C.R.C. #3658

Exxel Engineering

Found Leaded Stone/Set Monument

P.A. 345 1990 KENT COUNTY
PEER APPROVED 5/25/95
CHAIRMAN Randy Kolehose

This corner was originally approved by the Kent County Remonumentation Peer Group and monumented by Exxel Engineering
on 8/24/83 and was recorded per L.C.R.C. #3658.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

H-1

Found standard Kent County Monument 5.5' West of fence line running N-S and 1.0' North of a fence line running East and 3.0'
South of fence line running West per L.C.R.C. #3658 as set by Exxel Engineering in place of a leaded stone they found which
checks Williams & Works records of 1879. This point is on the Town line and is 6.67' West of the S 1/4 corner, Section 34, T6N,
R12W.

L.C.R.C. #3658

Remon. tag in SW'ly sde 22" Beech N35° W 61.22'

Kent County standard monument H-13 (set this same date) East 6.67'

The selected location is accepted by me and is generally accepted by professional surveyors as the best available evidence
of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

H-1

Standard Kent County Monument

Nail & K.C. remon. tag on W'ly side 22" Beech N 35° W 61.22'

K.C. Monument (H-13) East 6.67'

Nail & K.C. remon. tag on S face 8" Ash S 85° E 12.62'

Nail & K.C. remon. tag on E side 12" Maple S 20° W 50.76'

Signed by

Randy J. Kolehose
EARTH TECH

Date

8/21/95

Surveyor's Michigan License No.

25854

