

REMONUMENTATION
SEP 10 1995
\$7.00
\$2.00 COMMISSION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970
KENT COUNTY REMONUMENTATION

For corners in

Kent
(County)

Located in:

Corner Code #

1. Public Land Survey

T 5N R 12W

1-2

2. Property Controlling
in Section

S T R

3. Miscellaneous
Property in Sec.

S T R

4. Lot No. , Recorded Plat

5. Private Claims

REC. OF DEEDS

8625

STATE OF MICHIGAN
COUNTY OF KENT
RECEIVED FOR RECORD
95 AUG 28 AM 10:52

Register of Deeds Stamp & File Number

I, Randy Kolehose, in a field survey on April 7 19 95,
do hereby certify that under requirements of P.A. 74 Michigan P.A. of 1970, the corner points
mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required
in the current manual of survey instructions of the United States Department of the interior, Bureau of
Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3,
4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a
Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered,
found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

I-2	1831	G.L.O. Notes	Mullett	Set Post	P.A. 345 1990 KENT COUNTY
	1949	Wit. Map	K.C. Surveyor	Leaded Stone	PEER APPROVED 5/29/95
	1965	Wit. Map	K.C. Surveyor	3/4" Iron	CHAIRMAN <u>Harry Huber</u>
	1974	L.C.R.C. #679	Exxel Engineering	Found "T" Iron	
	1981	L.C.R.C. #1536	Exxel Engineering	Found "T" Iron/Set K.C. Monument	
	1991	L.C.R.C. #6326	Chris Marschall	K.C. Monument	

This corner was originally approved by the Kent County Remonumentation Peer Group and monumented by Exxel Engineering
on 12/16/80 and was recorded per L.C.R.C. #1536.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

I-2 Found standard Kent County Monument at intersection of C/L of Burlingame Avenue running N-S and 64th Street running E-
W per L.C.R.C.'s as shown above as set by Exxel Engineering in place of a "T" iron they found which checked L.C.R.C. #679
and K.C. Surveyor's Wit. Map.

L.C.R.C. #1536

PK nail on top South end 6' diameter CMP S53°E 34.77'
Nail & tag in NW sde 24" Maple (3' above ground) N62°E 60.52'
Nail & tag in W. sde 20" Walnut (3' above ground) N26°E 80.94'
Nail & tag in S. Sde 20" Walnut (2' above ground) N69°W 98.49'

L.C.R.C. #6326

PK nail on top South end 6' dia. CMP S 53 E 34.77'
Nail & Tag in NW sd. 26" Maple N 62 E 60.45'
Nail & Tag SE sd. 22" Walnut N 46 E 45.42'
Nail & Tag S sd. 22" Walnut N 69 W 98.48'
Nail & Tag NW sd. 22" Walnut N 26 E 80.87'
Nail & Tag SW sd. Guy Pole S 47 E 48.19'

The selected location is accepted by me and is generally accepted by professional surveyors as the best available evidence
of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

I-2 Standard Kent County Monument

PK nail on top South end 6' dia. CMP S 53° E 34.77'
Nail & K.C. remon. tag on NW side 26" Maple N 62° E 60.45'
Nail & K.C. remon. tag on SE side 22" Walnut N 46° E 45.42'
Nail & K.C. remon. tag on S side 22" Walnut N 69° W 98.48'
Nail & K.C. remon. tag on NW side 22" Walnut N 26° E 80.87'
Nail & K.C. remon. tag on SW side Guy pole S 47° E 48.19'

Signed by

Randy J. Kolehose
EARTH TECH

Date

8/21/95

Surveyor's Michigan License No.

25854

