

\$2.00  
\$2.00

SEP 1 8 1995

OFFICIAL

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970  
KENT COUNTY REMONUMENTATION

For corners in

Kent  
(County)

Located in:

Corner Code #

1. Public Land Survey

T 5N R 12W K-1

2. Property Controlling  
in Section

S T R

3. Miscellaneous  
Property in Sec.

S T R

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_

5. Private Claims \_\_\_\_\_

REG. OF DEEDS

95 AUG 28 AM 10:53

STATE OF MICHIGAN  
COUNTY OF KENT  
RECEIVED FOR RECORD

8644

Register of Deeds Stamp & File Number

I, Randy Kolehhouse, in a field survey on April 5 19 95,  
do hereby certify that under requirements of P.A. 74 Michigan P.A. of 1970, the corner points  
mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required  
in the current manual of survey instructions of the United States Department of the interior, Bureau of  
Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3,  
4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a  
Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered,  
found as expressed below:

NOTE: Not more than 4 corners; all in the same town and range, may be recorded  
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

K-1	1817	G.L.O. Notes	L. Lyon	Set Post
	1939	Wit. Map	K.C. Surveyor	Leaded Stone
	1961	Wit. Map	K.C. Surveyor	Leaded Stone
	1972	L.C.R.C. #207	Exxel Engineering	Found 1/2" Iron
	1977	L.C.R.C. #1053	J. McCloskey	Found R.R. Spike
	1981	L.C.R.C. #1821	Exxel Engineering	Found RR Spike/Set K.C. Monument
	1988	L.C.R.C. #4739	Olson, Meyers & May	K.C. Monument
	1992	L.C.R.C. #6621	J. Bueche	Found PK per L.C.R.C. #1821/Replaced with K.C. Monument

P.A. 345 1990 KENT COUNTY

PEER APPROVED 8/24/95

CHAIRMAN Harry Kube

This corner was originally approved by the Kent County Remonumentation Peer Group and monumented by Exxel Engineering  
on 5/4/81 and was recorded per L.C.R.C. #1821.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

K-1 Found standard Kent County Monument per L.C.R.C.'s #1821, #4739 and #6621 6' North of C/L of 60th Street running E-W  
and 3' West of the C/L of Clyde Park running N-S. This point is on the Town line 38.31' West of the SW corner Sec. 36, T6N  
R12W, as set by Exxel Engineering in place of a RR spike they found which checked L.C.R.C. #1053 and as reset by J.  
Bueche per L.C.R.C. #1821.

L.C.R.C. 1821

L.C.R.C. #6621

KC Monument at SE corner Section 35-6-12 East 38.40'

Nail & K.C. Remon. Tag in S side PP S 25° E 157.36'

L.C.R.C. #4739

Nail & K.C. Remon. Tag in S side PP N 70° E 96.13'

Nail & K.C. tag in S side P pole N 40° E 96.18'

SW cor. brick garg. to hse. N 50° W 133.13'

K.C. Mon (SE 35 T6N, R12W) East 38.40'

SW cor. CB header S 40° W 54.97'

Face curb E 33.3' ±

K.C. Mon. SW 36, 6-12 East 38.31'

The selected location is accepted by me and is generally accepted by professional surveyors as the best available evidence  
of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

K-1 Standard Kent County Monument

Nail & K.C. remon. tag on side P. pole S 25° E 157.36'

Nail & K.C. remon. tag on S side P. pole N 70° E 96.13'

SW cor. brick garg. to hse. N 50° W 133.13'

SW cor. CB header S 40° W 54.97'

Face curb E 33.3' ±

K.C. Mon. K-13 T6N R12W East 38.31'

Signed by Randy J. Kolehhouse

Date 8/21/95

EARTH TECH

Surveyor's Michigan License No. 25854

