

\$7.00
\$2.00 SEP 13 1995
COMMISSION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970
KENT COUNTY REMONUMENTATION

For corners in

Kent
(County)

Located in:

Corner Code #

- | | | | | | |
|-------------------------|---|----|---|-----|-----|
| 1. Public Land Survey | T | 5N | R | 12W | K-2 |
| | T | | R | | |
| | T | | R | | |
| | T | | R | | |
| 2. Property Controlling | S | | T | R | |
| in Section | S | | T | R | |
| 3. Miscellaneous | S | | T | R | |
| Property in Sec. | S | | T | R | |

STATE OF MICHIGAN
COUNTY OF KENT
RECEIVED FOR RECORD
95 AUG 28 AM 10:10
8645
REG. OF DEEDS

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, Randy Kolehouse, in a field survey on April 5 19 95,
do hereby certify that under requirements of P.A. 74 Michigan P.A. of 1970, the corner points
mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required
in the current manual of survey instructions of the United States Department of the Interior, Bureau of
Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3,
4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a
Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered,
found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

K-2	1831	G.L.O. Notes	Mullett	Set Post	P.A. 345 1990 KENT COUNTY
	1839	Wit. Map	K.C. Surveyor	Hole in Stone	PEER APPROVED 8/24/95
	1963	Wit. Map	K.C. Surveyor	Boat Spike	CHAIRMAN <u>Randy Kolehouse</u>
	1976	L.C.R.C. #1004	Nedervent, Medema, & Van Kooten	Found 3/4" Iron	
	1980	L.C.R.C. #1537	Exxel Engineering	Found 1" Iron/Set K.C. Monument	
	1991	L.C.R.C. #6344	Chris Marschall	K.C. Monument	
	1993	L.C.R.C. #6881	J. Bueche	K.C. Monument	

This corner was originally approved by the Kent County Remonumentation Peer Group and monumented by Exxel Engineering
on 12/10/80 and was recorded per L.C.R.C. #1537.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

K-2 Found standard Kent County Monument at the C/L intersection of Clyde Park Avenue running N-S and 64th Street running E-
W per L.C.R.C.'s 1537, 6344 and 6881 as set by Exxel Engineering in place of a 1" iron they found which checked L.C.R.C.
#1004 and K.C. Surveyor's Wit. Map - 1963.

L.C.R.C. #6344

L.C.R.C. #6881

Nail & Tag SE sd. U.P. S 46 W 68.60'
Centerline top nut Hydrant N 30 W 60.85'

Nail & Tag in SE side UP S 46° W 68.60'
C/L top nut hydrt. N 30° W 60.85'

The selected location is accepted by me and is generally accepted by professional surveyors as the best available evidence
of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

K-2 Standard Kent County Monument

Nail & K.C. remon. tag on SE side P. pole S 50° W 68.63'
Nail & K.C. remon. tag on NE side 18" Poplar S 47° E 98.75'
Nail & K.C. remon. tag on N side North Elm (in Clump of 5) East 41.88'
Nail & K.C. remon. tag on NW side 10" Tw. Maple N 56° E 67.83'

Signed by Randy J. Kolehouse
EARTH TECH

Date 8/21/95

Surveyor's Michigan License No. 25854

