

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970  
KENT COUNTY REMONUMENTATION

For corners in

Kent  
(County)

Located in:

Corner Code #

- |                                       |      |       |     |
|---------------------------------------|------|-------|-----|
| 1. Public Land Survey                 | T 5N | R 12W | K-4 |
|                                       | T    | R     |     |
|                                       | T    | R     |     |
|                                       | T    | R     |     |
| 2. Property Controlling<br>in Section | S    | T     | R   |
|                                       | S    | T     | R   |
| 3. Miscellaneous<br>Property in Sec.  | S    | T     | R   |
|                                       | S    | T     | R   |

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_
5. Private Claims \_\_\_\_\_

I, Randy Kolehouse, in a field survey on April 5 19 95,  
do hereby certify that under requirements of P.A. 74 Michigan P.A. of 1970, the corner points  
mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required  
in the current manual of survey instructions of the United States Department of the Interior, Bureau of  
Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3,  
4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a  
Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered,  
found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded  
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

K-4	1831	G.L.O. Notes	Mullett	Set Post
	1939	Wit. Map	K.C. Surveyor	Leaded Stone
	N/A	Wit. Map	K.C. Surveyor	Monument Box
	1975	L.C.R.C. #962	Exxel Engineering	Found Bt. Spk. in Mon. Box
	1980	L.C.R.C. #1535	Exxel Engineering	Found Bt. Spk. in Mon Box/Set K.C. Monument
	1987	L.C.R.C. #4528	J. Bueche	Reset K.C. Monument by Wit. L.C.R.C. 1535
	1991	L.C.R.C. #6346	Chris Marschall	K.C. Monument

P.A. 345 1930 KENT COUNTY

PEER APPROVED 8/24/95

CHAIRMAN Randy Kolehouse

This corner was originally approved by the Kent County Remonumentation Peer Group and monumented by Exxel Engineering  
on 12/16/80 and was recorded per L.C.R.C. #1535.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

K-4 Found standard Kent County Monument on the C/L of Clyde Park Avenue running N-S per L.C.R.C.'s #4528 and #6346 as set by  
Exxel Engineering in place of a boat spike in a monument box they found which checked L.C.R.C. #962 and K.C. Surveyor's Wit.  
Map.

L.C.R.C. #4528

L.C.R.C. #6346

NW cor. block fndn. of hse. (.5 above ground)  
S 40° E 97.42'  
PK in SW side MBT pole SE 49.38'  
PK in S. side CP pole W 44.63'

NW corner block Fndn. of Hse. (.5 above ground) S 40° E 97.35'  
Nail & Tag in S Sd U.P. S 85° W 44.85'  
Nail & Tag in SW Sd U.P. S 45° E 49.31'  
Nail & Tag in NW Sd U.P. N 45° E 78.51'  
Centerline top nut hydrant S 30° W 154.84'

The selected location is accepted by me and is generally accepted by professional surveyors as the best available evidence  
of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

K-4 Standard Kent County Monument

NW corner block fndn. of hse. (.5 above ground) S 40° E 97.35'  
Nail & K.C. remon. tag on S side Util. pole S 85° W 44.85'  
Nail & K.C. remon. tag on SW side Util. pole S 45° E 49.31'  
Nail & K.C. remon. tag on NW side Util. pole N 45° E 78.51'  
Centerline top nut hydrant S 30° W 154.84'

Signed by

Randy J. Kolehouse  
EARTH TECH

Date

8/21/95

Surveyor's Michigan License No.

25854