

SEP 1 8 1985

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970
KENT COUNTY REMONUMENTATION

For corners in

Kent (County)	Located in:	Corner Code #
1. Public Land Survey	T <u>5N</u> R <u>12W</u>	<u>K-12</u>
	T _____ R _____	_____
	T _____ R _____	_____
	T _____ R _____	_____
2. Property Controlling in Section	S _____ T _____ R _____	_____
	S _____ T _____ R _____	_____
3. Miscellaneous Property in Sec.	S _____ T _____ R _____	_____
	S _____ T _____ R _____	_____

STATE OF MICHIGAN
RECEIVED FOR RECORDATION
55 AUG 28 AM 10:54
55 AUG 28 AM 10:54
8655

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, Randy Kolehouse, in a field survey on April 6 19 95, do hereby certify that under requirements of P.A. 74 Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

K-12	1831	G.L.O. Notes	Mullett	Set Post
	1939	Wit. Map	K.C. Surveyor	Leaded Stone
	1981	L.C.R.C. #1813	Exxel Engineering	Found 3/4" Solid Steel Bar
	1991	L.C.R.C. #6354	Chris Marshall	K.C. Monument P.A. 345 1990 KENT COUNTY

PEER APPROVED 6/27/99
CHAIRMAN [Signature]

This corner was originally approved by the Kent County Remonumentation Peer Group and monumented by Exxel Engineering on 3/26/81 and was recorded per L.C.R.C. #1813.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

K-12 Found standard Kent County Monument in monument box at C/L intersection of Clyde Park Avenue running N-S and 104th Street running E-W per L.C.R.C. #6354 as set by Exxel Engineering in place of 3/4" solid steel bar they set which checked K.C.R.C. Wit. Map and Exxel records (Sept. 1972).

L.C.R.C. #6354

Nail & Tag NW sd. P.P. N 62° E 25.89'
Nail & Tag W sd. P.P. N 8° E 232.40'

The selected location is accepted by me and is generally accepted by professional surveyors as the best available evidence of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

K-12 Standard Kent County Monument in a Monument Box

Nail & K.C. remon. tag on NW side P. pole N 62° E 25.89'
Nail & K.C. remon. tag on W side P. pole N 05° E 232.40'
Nail & K.C. remon. tag on SE side 12" Poplar N 66° E 84.21'
C/L 3" metal fence cor. post S 05° E 215.48'

Signed by Randy J. Kolehouse Date 8/21/95

EARTH TECH

Surveyor's Michigan License No. 25854

