

\$7.00
\$2.00
SEP 18 1995
COMMISSION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970
KENT COUNTY REMONUMENTATION

For corners in

Kent
(County)

Located in:

Corner Code #

- | | | |
|------------------------------------|------------|-----|
| 1. Public Land Survey | T 5N R 12W | L-1 |
| | T R | |
| | T R | |
| | T R | |
| 2. Property Controlling in Section | S T R | |
| | S T R | |
| 3. Miscellaneous Property in Sec. | S T R | |
| | S T R | |

REC. OF DEEDS

Lucy Bond

95 AUG 28 AM 10:54

STATE OF MICHIGAN
COUNTY OF KENT
RECEIVED FOR RECORD

8657

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, Randy Kolehouse, in a field survey on April 5 19 95, do hereby certify that under requirements of P.A. 74 Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

L-1	1831	G.L.O. Notes	Mullett	Set Post
	N/A	Wit. Map	K.C. Surveyor	RR Iron in E R/W of RR
	1973	L.C.R.C. #645	Medema, Van Kooten & Assoc.	Found RR Iron in E R/W of RR
	1981	L.C.R.C. #1819	Exxel Engineering	Found RR Iron in E R/W of RR/Set K.C. Monument
	1988	L.C.R.C. #4740	J. Bueche	K.C. Monument P.A. 345 1990 KENT COUNTY

PEER APPROVED 6/27/95

CHAIRMAN Randy Kolehouse

This corner was originally approved by the Kent County Remonumentation Peer Group and monumented by Exxel Engineering on 2/20/81 and was recorded per L.C.R.C. #1819.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

- L-1 Found standard Kent County Monument 50' East of C/L RR tracks running N-S, 0.5' below grade, this point is on the Town line and is 28.75' West of the S 1/4 cor., Sec. 36, T6N R12W, per L.C.R.C.'s #1819 and #4740 as set by Exxel Engineering in place of a RR rail they found which checked L.C.R.C. #645 and Williams & Works' records.

L.C.R.C. #1819

L.C.R.C. #4740

C/L RR tracks West 49.24' (measured along Section line)
Nail & KC tag in West sde 22" Maple (3' high) N7° E 40.58'
S 1/4 corner, Section 36, T6N, R12W, (KC monument) East 28.75'

C/L RR tracks W 49.24' (mea along sec line)
New nail & KC tag in W sde 24" Maple (3' high) N 7 E 40.62'
S 1/4 cor sec 36, T6N, R12W, (KC Mon) E 28.75'

The selected location is accepted by me and is generally accepted by professional surveyors as the best available evidence of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

- L-1 Standard Kent County Monument

PK C/L RR tracks West 49.24'
Nail & K.C. remon. tag on W side 24" Maple N 07° E 40.62'
Nail & K.C. remon. tag on SE side 24" Oak N 20° E 161.19'
Nail & K.C. remon. tag on NW side 10" Blk. Oak S 05° W 42.79'
Standard K.C. Monument at L-13 T6N R12W East 28.75'

Signed by Randy J Kolehouse Date 8/21/95
EARTH TECH

Surveyor's Michigan License No. 25854

