

\$2.00
\$2.00

SEP 13 1995

COMMISSION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970
KENT COUNTY REMONUMENTATION

For corners in

Kent
(County)

Located in:

Corner Code #

- | | | | | | |
|---------------------------------------|---|----|---|-----|-----|
| 1. Public Land Survey | T | 5N | R | 12W | L-3 |
| | T | | R | | |
| | T | | R | | |
| | T | | R | | |
| 2. Property Controlling
in Section | S | | T | | R |
| | S | | T | | R |
| 3. Miscellaneous
Property in Sec. | S | | T | | R |
| | S | | T | | R |

REC. OF DEEDS

STATE OF MICHIGAN
COUNTY OF KENT
RECEIVED FOR RECORD
95 AUG 28 AM 10:54

8658

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, Randy Kolehouse, in a field survey on April 3 19 95, do hereby certify that under requirements of P.A. 74 Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

L-3	1831	G.L.O. Notes	Mullett	Set Post
	N/A	Wit. Map	K.C. Surveyor	1 1/2" Iron on Leaded Stone
	1973	L.C.R.C. #566	Medema, Van Kooten & Assoc.	Found 1" Iron in Mon. Box
	1981	L.C.R.C. #1611	Exxel Engineering	Found 1" Iron in Mon. Box/Set K.C. Monument
	1982	L.C.R.C. #3128	Exxel Engineering	Replaced K.C. Monument per Wit. L.C.R.C. #1611
	1992	L.C.R.C. #6356	Chris Marschall	K.C. Monument

P.A. 345 1990 KENT COUNTY

PEER APPROVED 6/27/95

CHAIRMAN Randy Kolehouse

This corner was originally approved by the Kent County Remonumentation Peer Group and monumented by Exxel Engineering on 11/2/82 and was recorded per L.C.R.C. #3128.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

- L-3 Found standard Kent County Monument on C/L of 68th Street running E-W and 2.5' West of West Rail RR tracks per L.C.R.C.'s #1611, #3128 and #6356 as set by Exxel Engineering in place of 1" iron in mon. box they found which checked L.C.R.C. #1611.

L.C.R.C. #3128

L.C.R.C. #6356

C/L top of hydrant N60°E 87.35'
W. edge of West rail N90°E 2.49'
Center of top of NE bolt on metal base of flasher
(2' above ground) S10°W 26.40'
Center of top of SW bolt on metal base of flasher
(2' above ground) N20°E 32.41'

Top of C/L Nut Hydrant N 74 E 87.35'
Center of top of SW Bolt on Metal base of
railroad flasher (2' above ground) N 40 E 32.39'
Center of top of NE Bolt on Metal base of
railroad flasher (2' above ground) S 16 W 26.37'
Nail & Tag N sd. P.P. N 52 W 58.81'
Nail & Tag NW sd. U.P. S 52 W 56.55'
West edge of West rail East 2.5' more or less

The selected location is accepted by me and is generally accepted by professional surveyors as the best available evidence of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

- L-3 Standard Kent County Monument
Top of C/L nut hydrant N 74° E 87.35'
Center of top of SW bolt on metal base of railroad flasher (2' above ground) N 40° E 32.39'
Center of top of NE bolt on metal base of railroad flasher (2' above ground) S 16° W 26.37'
Nail & K.C. remon. tag on N side P. pole N 52° W 58.81'
Nail & K.C. remon. tag on NW side Utl. pole S 52° W 56.55'
West edge of West rail East 2.5' more or less

Signed by Randy J. Kolehouse Date 8/21/95
EARTH TECH

Surveyor's Michigan License No. 25854

