

SEP 18 1995

CONFESSION

## LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

KENT COUNTY REMONUMENTATION

For corners in

Kent (County)	Located in:	Corner Code #
1. Public Land Survey	T 5N R 12W	L-7
	T R	
	T R	
	T R	
2. Property Controlling in Section	S T R	
	S T R	
3. Miscellaneous	S T R	
Property in Sec.	S T R	

STATE OF MICHIGAN  
COUNTY OF KENT  
RECEIVED FOR RECORD  
95 AUG 28 AM 10:55  
REG. OF DEEDS  
8660

Register of Deeds Stamp &amp; File Number

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_  
5. Private Claims \_\_\_\_\_

I, Randy Kolehouse, in a field survey on April 3 19 95, do hereby certify that under requirements of P.A. 74 Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

L-7	1831	G.L.O. Notes	Mullett	Set Post
	1945	Wit. Map	K.C. Surveyor	Leaded Stone
	1964	Wit. Map	K.C. Surveyor	Iron in Mon. Box
	1978	L.C.R.C. #1155	James Reda	Found 1/2" Solid Iron
	1980	L.C.R.C. #1522	Exxel Engineering	Found 1/2" Solid Iron/Set K.C. Monument
	1991	L.C.R.C. #6358	Chris Marshall	K.C. Monument

This corner was originally approved by the Kent County Remonumentation Peer Group and monumented by Exxel Engineering on 11/25/1980 and was recorded per L.C.R.C. #1522.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

- L-7 Found standard Kent County Monument 4' South of back of curb South of 84th Street per L.C.R.C.'s #1522 and #6358 as set by Exxel Engineering in place of 1/2" solid iron they found which checked L.C.R.C.'s #24 and #1155 and K.C. Wit. Map.

L.C.R.C. #1522

L.C.R.C. #6358

Nail & K.C. remon tag (2' above ground) in SW'ly sde  
20" Walnut S35°E 36.95'  
Nail & K.C. remon tag (2' above ground) in SE'ly sde  
36" Walnut S60°W 66.86'  
Leaded stone South 31.33'  
C/L storm manhole cover N65°E 59.54'  
SE corner hse # 407 (brick face) N5°W 129.29'  
C/L 84th Street North 29.5'

Nail & K.C. remon. tag (2' above ground) in SW'ly sde  
20" Walnut S 35 E 39.95'  
Nail & K.C. remon tag (2' above ground) in SE'ly sde  
36" Walnut S 60 W 66.86'  
Leaded stone South 31.33'  
Centerline storm manhole cover N 65 E 59.54'  
SE corner hse # 407 (brick face) N 5 W 129.29'  
Centerline 84th Street North 29.5'

The selected location is accepted by me and is generally accepted by professional surveyors as the best available evidence of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

L-7 Standard Kent County Monument

Nail & K.C. remon. tag (2' above ground) in SW'ly side 20" Walnut S 35° E 39.95'  
Nail & K.C. remon tag (2' above ground) in SE'ly side 36" Walnut S 60° W 66.86'  
Centerline storm manhole cover N 65° E 59.54'  
SE corner hse #407 (brick face) N 5° W 129.29'  
Centerline 84th Street North 29.5'

Signed by Randy J. Kolehouse Date 8/21/95

EARTH TECH

Surveyor's Michigan License No. 25854

