

\$7.00  
\$2.00

SURVEY &  
MONUMENTATION

JAN 23 1996

Seq. 2

LAND CORNER RECORDATION CERTIFICATE  
COMMISSION Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Kent  
(County)

Located in:

Corner Code #

1. Public Land Survey T 5N R 12W F-10  
T R  
T R  
T R  
2. Property Controlling S T R  
in Section S T R  
3. Miscellaneous S T R  
Property in Sec. S T R

4. Lot No. , Recorded Plat  
5. Private Claims

STATE OF MICHIGAN  
COUNTY OF KENT  
RECEIVED FOR RECORD  
95 DEC 28 PM 2:18  
REG. OF DEEDS  
8887  
Register of Deeds Stamp & File Number

I, Randy Kolehhouse, in a field survey on April 20 19 95, do hereby certify that under requirements of P.A. 74 Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

F-10 This corner was not originally set by the G.L.O.

1994 L.C.R.C. #6892 Jonker Land Surveys Set Capped Rerod at Int. of 1/4 Lines

P.A. 345 1990 KENT COUNTY

PEER APPROVED 8/24/95

CHAIRMAN Randy Kolehhouse

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

F-10 Found capped iron at fence corner of fences running North, South, and West per L.C.R.C. #6892. Iron is 0.1' South of the intersection of 1/4 lines. Accepted iron for Center Section.

L.C.R.C. #6892

Set Spk in the N. side 30" Twin Maple Az. 270° 24.12'  
Set Spk in the E. side 24" Cherry Az. 190° 28.70'  
Set Spk in the NE side 14" Maple Az. 320° 49.00'  
Set Spk in the W. side 12" Cherry Az. 0° 10.82'

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

F-10 Replaced capped iron with a standard 4" x 30" Kent County Monument

Nail & K.C. remon. tag in N side 30" Twin Maple West 24.12'  
Nail & K.C. remon. tag in E side 24" Cherry S 10° W 28.70'  
Nail & K.C. remon. tag in NE side 14" Maple N 40° W 49.00'  
Nail & K.C. remon. tag in W side 12" Cherry North 10.82'  
Fence corner 1.8' West

Signed by Randy J. Kolehhouse

EARTH TECH

Date 12/22/95

Surveyor's Michigan License No. 25854

