

JAN 23 1996

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970  
COMMISSION KENT COUNTY REMONUMENTATION

For corners in

Kent  
(County)

Located in:

Corner Code #

1. Public Land Survey

T 5N R 12W

H-10

2. Property Controlling  
in Section

S      T      R       
S      T      R     

3. Miscellaneous  
Property in Sec.

S      T      R       
S      T      R     

4. Lot No.                 , Recorded Plat                 

5. Private Claims   

I, Randy Kolehhouse, in a field survey on April 7 19 95,  
do hereby certify that under requirements of P.A. 74 Michigan P.A. of 1970, the corner points  
mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required  
in the current manual of survey instructions of the United States Department of the interior, Bureau of  
Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3,  
4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a  
Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered,  
found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded  
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

H-10 This corner was not originally set by the G.L.O.

1914-1927 Survey Notes  
1978 L.C.R.C. #1201

Williams & Works  
Nederveld & Jonker

Found and Accepted Iron  
Found and Accepted 1" Iron

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

H-10 Found 1" iron pipe 4' West of C/L of Celery Avenue per L.C.R.C. #1201. Measurements to the E 1/4, W 1/4 and N 1/4 check  
Jonker Land Surveys  $\pm 0.1'$ . Measurements to the S 1/4 check Jonker Land Surveys  $\pm 0.5'$ . This iron appears to be 10' M/L  
West of iron used by Williams & Works' 1914-1927 survey notes (iron not found). This iron is 0.1' North and 0.2' West of the  
intersection of 1/4 lines. Accepted iron as Center Section.

L.C.R.C. #1201

Nail in N side P. pole East 35.27'  
SW cor. hse. fndn. N 70° E 71.35'

P.A. 345 1990 KENT COUNTY

PEER APPROVED 8/24/95

CHAIRMAN Harry Stuber

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

H-10 Replaced iron with a standard 4" x 30" Kent County Monument

Nail & K.C. remon. tag in W side 24" Maple N 25° E 66.48'  
Nail & K.C. remon. tag in NE side 48" Maple N 30° W 45.57'  
PK nail in W end 18" Clump S 75° W 18.36'  
Nail in N side P. pole East 35.27'  
SW cor. hse. fndn. N 70° E 71.35'

Signed by Randy J. Kolehhouse  
EARTH TECH

Date 12/22/95

Surveyor's Michigan License No. 25854

Seq. 2

REG. OF DEEDS

Lucy Stuber

95 DEC 28 PM 2:20

STATE OF MICHIGAN  
COUNTY OF KENT  
RECEIVED FOR RECORD

8891

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													