

# LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A. 1970

LOWELL TOWNSHIP

FOR CORNERS OF --	LOCATED IN --	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____ T. 6 N. R. 9 W.		K-3 (Wit. cor's.)
2. PROPERTY CONTROLLING IN SECTION _____, T. _____ N. S. R. _____ E. W.		Other Code
3. MISCELLANEOUS PROPERTY IN SECTION _____, T. _____ N. S. R. _____ E. W.		#1
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

6862 A  
REGISTER OF DEEDS STAMP AND  
FILING NUMBER

I, Kevin Roosien, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on \_\_\_\_\_, 19\_\_\_\_, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on \_\_\_\_\_, 19\_\_\_\_, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

K-3 No Record - corner falls in the Grand River (GLO)  
L.C.R.C. #5169 by Wallace Glaza sets p.k. in bridge deck by double proportionate measurement  
various surveys by W&W establish section lines north and south of corner K-3, on each side of the Grand River

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

After extensive research and field investigation, I found the historical lines referred to by the old W&W information, which matched other monumentation in the field, including old plats and right of way irons. The historical lines were honored, and witness corners set on the north and south sides of the river. The section corner common to sections 1 and 2 intersects 8.82 feet west of the section corner common to sections 11 and 12. The corner set by Glaza which falls in the bridge deck is not being honored, as decided by the peer group. (See back of cert. for add.)

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

K-3 - North Witness Monument:  
Set std. K.C. Monument in gravel  
Wit's: Set K.C. Nail in tag top of guard rail post S30°W 64.14'  
-Set K.C. Nail in tag, top of guard rail post S20°W 95.63'  
-P.K. nail in c/l bit. West 16.20'  
-c/l E. leg sign post N1°W 89.03'  
-Kent County Monument N. 2,221.19'  
-Capped iron N. 900.0' on sec. line  
- (wit. cor. is on sec. line)

K-3 - (South Witness Monument)  
Set std. K.C. Mon. in c/l of Grand River Drive in bit. on section line  
- rerod in c/l "X" ENE 8.87'  
- set nit E. side 36" Maple N5°W 126.8'  
- set nit S. side P.Pole N70°E 107.00'  
- set nit S. side P.Pole S50°E 43.12'  
- " " N. " " " N80°W 66.57'  
see back side for section measurements and other information.  
(sun shot not available)

SIGNED BY Kevin Roosien

DATE 12/20/93

SURVEYOR'S MICHIGAN REGISTRATION NO. 31604

(SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY \_\_\_\_\_ CHIEF OF SURVEY PARTY

DATE \_\_\_\_\_

APPROVED AND SIGNED BY \_\_\_\_\_ MICHIGAN REGISTERED LAND SURVEYOR

DATE \_\_\_\_\_

SURVEYOR'S MICHIGAN REGISTRATION NO. \_\_\_\_\_



