

SURVEY
REMONUMENTATION

SEP 18 1995

COMMISSION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970
KENT COUNTY REMONUMENTATION

STATE OF MICHIGAN
COUNTY OF KENT
RECEIVED FOR RECORD

95 MAR 24 AM 11:15

For corners in

Kent
(County)

Located in:

Corner Code #

- | | | | |
|---------------------------------------|-------------|--------------|------------------|
| 1. Public Land Survey | T <u>6N</u> | R <u>12W</u> | Ref. Mon. |
| | T | R | 608.0' E. of B-5 |
| | T | R | |
| | T | R | |
| 2. Property Controlling
in Section | S | T | R |
| | S | T | R |
| 3. Miscellaneous
Property in Sec. | S | T | R |
| | S | T | R |

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, Randy Kolehouse, in a field survey on October 8 19 94,
do hereby certify that under requirements of P.A. 74 Michigan P.A. of 1970, the corner points mentioned
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the
current manual of survey instructions of the United States Department of the Interior, Bureau of Land
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a
Court of Law; established, re-established, monumented, re-monumented, recovered, found as
expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

B-5 This corner was not established by the G.L.O. The south line of Section 7 was not run. Old Williams & Works survey
records show only a temporary point.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

B-5 Computed the location of this corner as follows: On line of the N 1/4 corner and Center Section extended South at
2636.60' South of the Center Section (this is double of 1/8 line dist. shown on old Williams & Works survey from Center
South of 1318.3'. Compute corner to be 2680.24' East of the SW corner of Section 7. The line is within 00°00'32" of being
parallel with the north line of Section. Corner falls in a swamp (2' water ±)

Set reference monument 608.00' East of computed corner location on line with C-5.

P.A. 345 1990 KENT COUNTY

PEER APPROVED 9/12/94
CHAIRMAN Randy Kolehouse

The selected location is accepted by me and is generally accepted by professional surveyors as the best available evidence
of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

B-5 Standard 4" x 30" Kent County Monument.

Nail & K.C. remon. tag in S side 16" Willow N 90° E 89.33'
Nail & K.C. remon. tag in S side 14" Ash N 90° W 155.98'
Nail & K.C. remon. tag in NE side 14" Maple N 70° W 112.11'
Nail & K.C. remon. tag in NE side 18" Maple N 60° W 98.04'
Nail & K.C. remon. tag in E side 14" Maple N 05° W 130.62'
Edge of Grand River SE 150' ±

Note above witnesses are approximately 5-6' above ground level.

Signed by Randy J. Kolehouse

Date

3/20/95

Surveyor's Michigan License No.

25854

