

SURVEY & REMONUMENTATION

Kent County Remonumentation

STATE OF MICHIGAN
COUNTY OF KENT
RECEIVED FOR RECORD

SEP 03 1999

LAND CORNER RECORDATION CERTIFICATE 94 NOV 29 AM 9:18
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in
Kent

SECTION

(County)

Located In:

Corner Code ##

1. Public Land Survey

T	_____	R	_____
T	_____	R	_____
T	_____	R	_____
T	_____	R	_____
2. Property Controlling
in Section

S	_____	T	_____	R	_____
S	_____	T	6N	R	12W
3. Miscellaneous
Property in Sec.

S	_____	T	_____	R	_____
S	_____	T	_____	R	_____

46.92' W of D-3

Reference

Monument

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, Randy Kolehouse, in a field survey on June 8, 1994,
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the
current manual of survey instructions of the United States Department of the Interior, Bureau of Land
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a
Court of Law; established, re-established, monumented, re-monumented, recovered, found as
expressed below:

**NOTE: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.**

A. Description of original monument and accessories and/or subsequent restoration:

D-3	1831	G.L.O. Notes	L. Lyon	Set Post
	1944	Wit. Map	K.C. Surveyor	Iron
	1981	L.C.R.C. #3555	Medema Van Kooten	Set Ref. Iron
	1990	L.C.R.C. #5325	John C. Bueche	Fnd. Ref. Iron/Set Ref. Mon.

P.A. 345 1990 KENT COUNTY

PEER APPROVED 9/22/99
CHAIRMAN Randy Kolehouse

The position of this corner was previously approved by the Kent County Remonumentation Peer Group monumented by John
C. Bueche on 3/20/90 and was recorded per L.C.R.C. #5325.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

D-3 Found K.C. Monument per L.C.R.C. #5325 which was set 46.92' West of D-3 by John Bueche in place of a ref. iron set by
Medema Van Kooten Assoc. using survey records of Williams & Works and recorded in L.C.R.C. #3555 by Medema Van Kooten.

L.C.R.C. #5325

Tag & nail E. side 12" Elm S 45° E 19.49'
Tag & nail E side 10" Elm S 10° E 19.66'
Tag & nail N side 10" Elm S 25° W 32.90'
Tag & nail S side 10" Elm S 55° W 15.70'
Tag & nail W side 6" Elm N 80° W 15.67'

The selected location is accepted by me and is generally accepted by professional surveyors as the best available evidence
of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

D-3 Standard Kent County Monument

Nail & K.C. remon. tag in E. side 12" Elm S 45° E 19.49'
Nail & K.C. remon. tag in E side 10" Elm S 10° E 19.66'
Nail & K.C. remon. tag in N side 10" Elm S 25° W 32.90'
Nail & K.C. remon. tag in S side 10" Elm S 55° W 15.70'
Nail & K.C. remon. tag in W side 6" Elm N 80° W 15.67'



Signed by Randy J. Kolehouse

Date 11/21/94

25854

Surveyor's Michigan License No. _____

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971
REVISED MAY 14, 1975
REVISED JAN., 1983