

SURVEY & REMONUMENTATION

SEP 03 1999

SECTION

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970 KENT COUNTY REMONUMENTATION

STATE OF MICHIGAN
COUNTY OF KENT
RECEIVED FOR RECORD

94 DEC -6 AM 8:59

For corners in

Kent
(County)

Located in:

Corner Code #

- | | | | |
|------------------------------------|-------------|--------------|---------------------------|
| 1. Public Land Survey | T <u>6N</u> | R <u>12W</u> | <u>L-12</u> |
| | T | R | |
| | T | R | <u>Reference Monument</u> |
| | T | R | <u>30.00' East</u> |
| 2. Property Controlling in Section | S | T | R |
| | S | T | R |
| 3. Miscellaneous Property in Sec. | S | T | R |
| | S | T | R |

Lucy Bond
REG. OF DEEDS
**Prop Control 1
other code #5**
7754

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, Randy Kolehose, in a field survey on October 10 19 94, do hereby certify that under requirements of P.A. 74 Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

L-12 This corner was not originally set by the G.L.O.

1949	Survey Records	Williams & Works	Set Iron at 1/4 Lines
1949-84	Survey Records	Williams & Works	Intersection 1/4 Lines
N/A	Survey Records	Exxel Engineering	Intersection 1/4 Lines

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

L-12 Center Section falls in center of Buck Creek. No corner found, per Williams & Works records the center is 13.42' North of bt. spike in bridge on 56th Street (now removed). Set point for Center Section at intersection of 1/4 lines per Williams & Works survey records. This point checks Exxel Engineering survey records.

P.A. 345 1990 KENT COUNTY
PEER APPROVED 10/12/99
CHAIRMAN *Harry J. Huber*

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

L-12 Reference Monument (Standard K.C. Monument) 30.00' East of the Center of Section 36 on E-W 1/4 line.

Witnesses to Reference Monument

SE corner brick fndn. N 66° W 82.31'
Nail & tag in NE side t. pole S 61° E 58.64'
P.K. nail & tag in SE side G. Pole N 58° E 58.93'
Nail & tag in SE side p. pole S 40° W 62.81'
Nail & K.C. remon. tag in NE side p. pole S 71° E 105.73'
C/L hydrant N 34° E 76.49'



Signed by *Randy J. Kolehose*

Date 12/1/94

Surveyor's Michigan License No. 25854