

**SURVEY &
REMONUMENTATION**

MAR 08 1999

SECTION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970
KENT COUNTY REMONUMENTATION

other code # 2

For corners in

Kent
(County)

Located in: Vergennes
Township

Corner Code #

1. Public Land Survey

T 7N R 9W D-6W
T R
T R Witness Monument
T R 396.24' West of D-6

2. Property Controlling
in Section

S T R
S T R

3. Miscellaneous
Property in Sec.

S T R
S T R

4. Lot No. , Recorded Plat

5. Private Claims

I, Randy Kolehouse, in a field survey on December 3 19 98,
do hereby certify that under requirements of P.A. 74 Michigan P.A. of 1970, the corner points
mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required
in the current manual of survey instructions of the United States Department of the interior, Bureau of
Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3,
4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a
Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered,
found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

D-6W This corner was not originally set by the G.L.O.

No information on record for this corner.

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6		5	4	3	2	1						
3													
4	7		8	9	10	11	12						
5													
6	18		17	16	15	14	13						
7													
8	19		20	21	22	23	24						
9													
10	30		29	28	27	26	25						
11													
12	31		32	33	34	35	36						
13													

P.A. 345 1990 KENT COUNTY

PEER APPROVED 12/24/98

CHAIRMAN Randy Kolehouse

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

D-6W Corner falls within swamp. Held calculated center at intersection of 1/4 lines. Set witness monument on the East-West 1/4
line 396.24' West of the intersection of 1/4 lines at top of bank 100' ± West of the West edge of swamp and 150' ± North of
the South edge of woods.

The selected location is accepted by me and is generally accepted by professional surveyors as the best available evidence
of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

D-6W Set a Kent County Witness Monument

Nail & K.C. remon. tag on S'y side 18" Oak N 35° W 10.20'
Nail & K.C. remon. tag on S side 18" Oak N 82° E 14.15'
Nail & K.C. remon. tag on NE'y side 18" Oak S 47° E 28.90'
Nail & K.C. remon. tag on E'y side 18" Oak S 15° E 25.32'
West edge of swamp, East 100' ±
South edge of woods, South 150' ±

Signed by Randy J. Kolehouse

EARTH TECH

Date 12/14/98

Surveyor's Michigan License No. 25854

