

SURVEY & REMONUMENTATION

MAR 08 1999

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970 KENT COUNTY REMONUMENTATION

For corners in

SECTION

Kent
(County)

Located in: Vergennes
Township

Corner Code #

1. Public Land Survey

T	7N	R	9W	D-6N
T		R		
T		R		465.52' North of D-6
T		R		
2. Property Controlling in Section

S		T		R	
S		T		R	
3. Miscellaneous Property in Sec.

S		T		R	
S		T		R	

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, Randy Kolehouse, in a field survey on December 3, 19 98, do hereby certify that under requirements of P.A. 74 Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

D-6N This corner was not originally set by the G.L.O.

No information on record for this corner.

P.A. 345 1990 KENT COUNTY

PEER APPROVED 9/24/98

CHAIRMAN [Signature]

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

D-6N Corner falls within swamp. Held calculated center at intersection of 1/4 lines. Set witness monument on the North-South 1/4 line 465.52' North of the intersection of 1/4 lines, 200' ± North of the North edge of swamp, and 30' ± West of old North-South fence line and tree row.

The selected location is accepted by me and is generally accepted by professional surveyors as the best available evidence of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

D-6N Set a Kent County Witness Monument

- Nail & K.C. remon. tag on SE side 10" Oak N 44° E 15.34'
- Nail & K.C. remon. tag on NE side 16" Oak S 46° E 6.29'
- Nail & K.C. remon. tag on W'ly side 10" Oak S 23° W 5.68'
- Nail & K.C. remon. tag on NE'ly side 16" Oak N 62° W 21.83'
- North edge of swamp, South 200' ±
- Old fence line and tree row running N-S, East 30' ±

by Randy J. Kolehouse Date 12/14/98

EARTH TECH

Michigan License No. 25854

