

SURVEY & REMONUMENTATION

MAR 08 1999

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970 KENT COUNTY REMONUMENTATION

SECTION

For corners in

Kent
(County)

Located in: Vergennes
Township

Corner Code #

1. Public Land Survey

T	7N	R	9W	J-9N
T		R		
T		R		Witness Monument
T		R		
2. Property Controlling in Section

S	T	R		
S	T	R		
3. Miscellaneous Property in Sec.

S	T	R		
S	T	R		

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

REG. OF DEEDS

38 DEC 14 AM 8:00

STATE OF MICHIGAN
COUNTY OF KENT
RECEIVED FOR RECORD

other code # 5
11030

Register of Deeds Stamp & File Number

I, Randy Kolehouse, in a field survey on January 25 19 98, do hereby certify that under requirements of P.A. 74 Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

J-9	1838	G.L.O. Notes	N. Brookfield	Point in River
	1989	L.C.R.C. #5222	John Bueche	Set K.C. Witness Monument
	1995	L.C.R.C. #8248	William Byl	K.C. Witness Monument

P.A. 345 1900 KENT COUNTY
PEER APPROVED 2/19/98
CHAIRMAN John Bueche

This corner was originally approved by the Kent County Remonumentation Peer Group and monumented by John Bueche on 10/10/89 and was recorded per L.C.R.C. 5222.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

J-9 Found a Standard Kent County Witness Monument 28' ± North of the Flat River 61.15' North of J-9 per L.C.R.C.'s #5222 and #8248 as set by John Bueche on the North and South 1/4 line of Section 23.

L.C.R.C. #5222

L.C.R.C. #8248

Nail & Remon tag in W side 10" Poplar N 15° E 22.63'
Nail & Remon tag in S side 16" Oak N 90° E 46.3'
Nail & Remon tag in W side 8" Ash S 5° W 18.78'
Nail & Remon tag in S side 12" Ash N 90° W 29.43'
Nail & Remon tag in SE side dbl. 20" Poplar N 60° E 9.65'
Nail & Remon tag in E side 30" Pplar N 15° W 3.05'

Nail & KC Remon. Tag W. side 10" Poplar N 15° E 22.60' (m. 22.59')
Nail & KC Remon. Tag S. side 24" Oak N 90° E 46.71' (m. 46.74')
Nail & KC Remon. Tag W. side 8" Ash S 05° W 18.76' (m. 18.78')
Nail & KC Remon. Tag S. side 12" Ash N 90° W 29.43' (m. 29.38')
Nail & KC Remon. Tag SE side dbl. 24" Poplar N 60° E 9.17'
Nail & KC Remon. Tag E. side 30" Poplar N 15° W 3.01' (m. 3.02')

The selected location is accepted by me and is generally accepted by professional surveyors as the best available evidence of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

J-9 Standard Kent County Witness Monument

Nail & K.C. remon. tag on W side 10" Poplar N 15° E 22.59'
Nail & K.C. remon. tag on S side 24" Oak N 90° E 46.74'
Nail & K.C. remon. tag on W side 8" Ash S 05° W 18.78'
Nail & K.C. remon. tag on S side 12" Ash N 90° W 29.38'
Nail & K.C. remon. tag on SE side dbl. 24" Poplar N 60° E 9.17'
Nail & K.C. remon. tag on E side 30" Poplar N 15° W 3.02'

Signed by Randy J. Kolehouse

Date 12/14/98

EARTH TECH

Surveyor's Michigan License No. 25854

