

# SURVEY & REMONUMENTATION

MAR 03 1998

## LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970 KENT COUNTY REMONUMENTATION

For corners in

SECTION

Kent	Located in:	Ada	Corner Code #
(County)		Township	
1. Public Land Survey	T	R	C-7
	T	R	
	T	R	
	T	R	
2. Property Controlling in Section	S	T 7N R 10W	2399.19 North of C-8
	S	T	R
3. Miscellaneous Property in Sec.	S	T	R
	S	T	R

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_  
5. Private Claims \_\_\_\_\_

I, Randy Kolehouse, in a field survey on November 14 19 97, do hereby certify that under requirements of P.A. 74 Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

C-7 1831 G.L.O. Notes Mullett Set Post  
1988 L.C.R.C. #4941 Exxel Engineering Set Witness Corners

This corner was originally approved by the Kent County Remonumentation Peer Group and monumented by Exxel Engineering on 2/11/88 and was recorded per L.C.R.C. #4941.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

C-7 Found a Standard Kent County Monument 2.5' South of the waters edge of the Grand River per L.C.R.C. #4941 as set by Exxel Engineering.

L.C.R.C. #4941

Nail & tag SE sde 24" Oak N 45° E 19.71' (m. 19.45')  
Nail & tag S sde 24" Oak S 65° E 71.27' (m. 71.30')  
Nail & tag SW sde Triple 16" Oak N 35° W 11.00' (m. 10.93')  
Nail & tag S sde 8" and 12" Tw. Oak N 65° W 55.93' (m. 55.90')  
Waters edge NE 25' ±

The selected location is accepted by me and is generally accepted by professional surveyors as the best available evidence of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

C-7 Standard Kent County Monument

Nail & K.C. remon. tag on SE side 24" Oak N 45° E 19.45'  
Nail & K.C. remon. tag on S side 24" Oak S 65° E 71.30'  
Nail & K.C. remon. tag on SW side Tri. 16" Oak N 35° W 10.93'  
Nail & K.C. remon. tag on S side 8" & 12" Twin Oak N 65° W 55.90'

Signed by Randy J. Kolehouse

EARTH TECH

Date

11/28/97

Surveyor's Michigan License No. 25854

Other # 16  
97 DEC 15 AM 10:41  
STATE OF MICHIGAN  
COUNTY OF KENT  
RECEIVED FOR RECORD  
REG. OF DEEDS  
10352

Register of Deeds Stamp & File Number

A	B	C	D	E	F	G	H	I	J	K	L	N
2	6	5	4	3	2	1						
3												
4	7	8	9	10	11	12						
5												
6	18	17	16	15	14	13						
7												
8	19	20	21	22	23	24						
9												
10	30	29	28	27	26	25						
11												
12	31	32	33	34	35	36						
13												

P.A. 345 1990 KENT COUNTY  
PEER APPROVED 11/28/97  
CHAIRMAN Randy Kolehouse

