

1729 0 8 1999

Fo	r corners in	SECTION	Fi	iling Require	R RECORDATION CERT pment of Act 74, Mich. P UNTY REMONUMENTATI	P.A. 1970 RB C RB RESERVE	
	Kent (County)	·····	Located i	n: Grattan Township	Corner Code #	OF DE COMME	
1.	Public Land Survey		T <u>8N</u> T T	R	I-10S Witness Monument	other code #11	
2.	Property Controlling	s					
	in Section	s	_ T	. R		10984	
3.	Miscellaneous	s	_ T	R			
	Property in Sec.	s	_ Т	. R		Register of Deeds Stamp & File Number	_
4.	Lot No	_, Recorded	Plat				
5.	Private Claims					A B C D E F G H I J K	
						2 6 5 4 3 2	_
	Daniel (Katal					3	-

in a field survey on February 10 do hereby certify that under requirements of P.A. 74 Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate

- Description of original monument and accessories and/or subsequent restoration:
- This comer was not originally set by the G.L.O.

1992 L.C.R.C. #6554A

1992

L.C.R.C. #6557

John Bueche John Bueche Set Reference Monument

Set K.C. Monument

P.A. 345 1990 KENT COUNTY PEER APPROVED 9/24/9/8

This corner was originally approved by the Kent County Remonumentation Peer Group and monumented by John Bueche in August 1992 and was recorded per L.C.R.C. 6557.

- В. Description of corner evidence found and/or method applied in restoring or reestablishing corner:
- Found a Standard Kent County Witness Monument on the South side of Lalley Lake 6' + South of the C/L of a two-track running East and West per L.C.R.C.'s #6554A and #6557 as set by John Bueche on the section line between Sections 26 and 27, 1365.26' South of the 1/4 corner common to Sections 26 and 27.

L.C.R.C. #6554A

1365.26' South of the E 1/4 27 on East line of Sec. 27

L.C.R.C. #6557

Nail & K.C. Remon. Tag in S side 16" Hickory N 60° W 28.50'

Nail & K.C. Remon. Tag in W side 12" Hickory S 30° W 19.25' (m. 19.23')

Nail & K.C. Remon. Tag in W side 18" Ash S 80° E 23.59' (m. 23.65')

C/L 2 track E-W, North 6' +/-

The selected location is accepted by me and is generally accepted by professional surveyors as the best available evidence of the position of the original corner.

- C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:
- Standard Kent County Witness Monument

Nail & K.C. remon. tag on S side 16" Hickory N 60° W 28.50'

Nail & K.C. remon. tag on W side 12" Hickory S 30° W 19.23'

Nail & K.C. remon. tag on SW side 18" Ash S 80° E 23.65'

Nail & K.C. remon. tag on E side 12" Hickory N 15° E 54.25'

C/L 2 track running E-W, North 6' ±

Signed by

KOLEHOUSE AND

Surveyor's Michigan License No.

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971 **REVISED MAY 14, 1975** REVISED JAN., 1983