## SURVEY & REMONUMENTATION



SEP 0 3 1999

## "other" code #13

For c	orners in	SECTION	Filing Requirement	of Act 74, Mich. P.A. 1970 REMONUMENTATION	\ 8 R S S S S S S S S S S S S S S S S S S
	Kent (County)	L		orner Gode #	OCI 23 REG. OF
1. F	Public Land Survey			E-10	W 9: 59
3. N	Property Controlling n Section Miscellaneous Property in Sec.	\$ \$	TR	В	10859 legister of Deeds Stamp & File Number
4. L 5. F	ot No	, Recorded P	at		
do he mention the Land 4 and Decree	ereby certify that uponed in lines 1 and current manual of Management or by 5 above were in ce of a Court of Le as expressed below:  Not more that on this certify  Description of or 1837 1880-1974 1951-1974 N/A 1944 1985 1994	under requiremen 2 above were in consurvey instructions a decree of a Coulonformance with saw; established, w:  n 4 corners, all icate.  riginal monument G.L.O. Notes Notes Notes Notes Witness Map L.C.R.C. #4298 L.C.R.C. #8020	ts of P.A. 74 Michigan P.A conformance with regulations as of the United States Depart of Law and/or that the corn the rules of the Michigan Boare-established, monumented in the same town and range at and accessories and/or so Cathcart  Williams & Works  Williams & Works  Williams & Works  Exxel Engineering  K.C. Surveyor  R. Kolehouse  Glaza & Associates	Set Post Leaded Stone in Swar Reference Iron Used Iron Lead Stone Set Witness Corner K.C. Witness Corner	2
B.	Description of co	orner evidence f	ound and/or method applie	ed in restoring or reestablishi	ing corner:
E-10	Northwest of the Kolehouse as a	C/L of Murray L witness monume	ake Road (bit.) running Nor	th to East per L.C.R.C.'s #42	) running Northwest and 100' ± 98 and #8020 as set by Randy Checked notes from Williams &
	Nail & K.C. Remon. Nail & K.C. Remon.	tag in SE side P.P	18" Quad Oaks S 20° W 90.00' ole S 65° W 75.02' 6" Elm N 45° W 82.43'	Nail & K.C. remon tag in SE s	#8020 le 1`4"-24" Quad.Oaks S20°W 89.90' (m. 89.82') ide Power Pole S65°W 75.02' (m. 75.05') side 10" Tri. Elm N45°W 82.13' (m. 82.12')
	The selected loca		- · · · · · · · · · · · · · · · · · · ·	epted by professional surveyo	rs as the best available evidence

of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

E-10 Standard Kent County Wilness Monument 165.0' South of E-10

Nail & K.C. remon. tag on E side 14" to 24" Quad Oaks S 20° W 89.82'

Nail & K.C. remon, tag on SE side P. pole S 65° W 75.05'

Nail & K.C. remon. tag on SW side triple 8" to 10" Elms N 45° W 82.12'

Nail & K.C. remon. tag on N side 8" Pine S 78° W 65.39'

C/L "X" of roads, Southeast 100±

EARTH TECH

RANDY J. KOLEHOUSE CONSCO LAND

Surveyor's Michigan License No.

Signed by

25854