

SURVEY & REMONUMENTATION

MAR 03 1998

SECTION

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970 KENT COUNTY REMONUMENTATION

For corners in

Kent
(County)

Located in: Cannon
Township

Corner Code #

1. Public Land Survey

T
T
T
T

R
R
R
R

2. Property Controlling
in Section

S T 8N R 10W

Reference Monument
892.82' West of M-12

3. Miscellaneous
Property in Sec.

S T R

4. Lot No. , Recorded Plat

5. Private Claims

I, Randy Kolehouse, in a field survey on October 25 19 97, do hereby certify that under requirements of P.A. 74 Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

M-12 1831 G.L.O. Notes Mullett Set Post
1993 L.C.R.C. #6734 T. Starr Set Witness Monument on East and West 1/4 Line

Note: This corner is common with A-12, T8N, R9W.

This corner was originally approved by the Kent County Remonumentation Peer Group and monumented by T. Starr on 3/3/93 and was recorded per L.C.R.C. #6734.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

M-12 Found a Standard Kent County Monument 80' East of bend in Bell Lake Drive (gravel) running West and South and 150' ± West of the West edge of Ratigan Lake per L.C.R.C. #6734 as set by T. Starr as a witness monument on the East and West 1/4 line.

L.C.R.C. #6734

Nail and Remon Tag in N. side Twin 12" Maple N 65° W 13.07' (m. 12.95')
Nail and Remon Tag in N. side Twin 14" Maple N 40° W 23.25'
Nail and Remon Tag in W. side 12" Cherry N 05° W 46.65' (m. 46.57')
Nail and Remon Tag in W. side 10" Maple N 40° E 31.49'
Nail and Remon Tag in S. side 10" Willow S 80° E 12.16'
Nail and Remon Tag in E. side 6" Willow S 35° E 17.00' (m. 17.10')

The selected location is accepted by me and is generally accepted by professional surveyors as the best available evidence of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

M-12 Standard Kent County Monument

Nail & K.C. remon. tag on N face Twin 12" Maple N 65° W 12.95'
Nail & K.C. remon. tag on N face Twin 14" Maple N 40° W 23.25'
Nail & K.C. remon. tag on W face 12" Cherry N 05° W 46.57'
Nail & K.C. remon. tag on W face 10" Maple N 40° E 31.49'
Nail & K.C. remon. tag on S face 10" Willow S 80° E 12.16'
Nail & K.C. remon. tag on E face 6" Willow S 35° E 17.10'

Signed by Randy J. Kolehouse

Date 11/24/97

Surveyor's Michigan License No. 25854

