

FEB 14 1997

**KENT COUNTY REMONUMENTATION**

**COMMISSION**

**LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970**

For corners in  
**KENT COUNTY**  
(County)

Located In:

Corner Code #

1. Public Land Survey

T R

#10

T R

T R

T R

2. Property Controlling  
in Section

S 26 T 8N R 11W

Wit. Mon. on

N. line Sec. 26

3. Miscellaneous

S T R

Property in Section

S T R

4. Lot No. , Recorded Plat

5. Private Claims

REG. OF DEEDS

*W. J. Bond*

96 MAR 20 AM 8:59

STATE OF MICHIGAN  
COUNTY OF KENT  
RECEIVED FOR RECORD

**9108**

Register of Deeds Stamp & File Number

I, **Kirk Breitels**, in a field survey on **Jan. 25**, 19 **96**,

do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Professional Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

**NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.**

A. Description of original monument and accessories and/or subsequent restoration:

1837 GLO Whitcomb Set Meander Post 39 chains East  
of the N 1/4 corner of Sec. 26  
1992 LCRC #6615 Marschall Set Kent County Witness Monument on  
N. line of Sec. 26.

The position of this corner was previously approved by the Kent County Remonumentation Peer Group, monumented (Witness Monument) by Chris Marschall on 10/27/92 and was recorded per LCRC #6615.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found Standard Kent County Witness Monument per witnesses from above LCRC as set by Chris Marschall.

**LCRC #6615**

Nail & KC Remon. tag 5' high SW side 8" Hackberry S77°E 19.98'  
Nail & KC Remon. tag SW side 8" Oak S47°E 69.51'  
Nail & KC Remon. tag 7' high SW side 18" Oak N43°W 125.51'  
NE cor. hse. N51°W 268.82'  
SE cor. hse. N68°W 299.60'  
Top of bank is NE 4'±  
River bank is NE 10'±

P.A. 345 1990 KENT COUNTY  
PEER APPROVED 3/7/96  
CHAIRMAN *Harry Shupere*

The selected location is accepted by me and is generally accepted by professional surveyors as the best available location of the corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Standard Kent Co. Witness Monument

Nail & KC Remon. tag 5' high SW side 8" Hackberry S77°E 19.98'  
Nail & KC Remon. tag SW side 8" Oak S47°E 69.54'  
Nail & KC Remon. tag 7' high SW side 18" Oak N43°W 125.54'  
NE cor. hse. N51°W 268.76'  
SE cor. hse. N68°W 299.69'  
Top of bank is NE 4'±  
River bank is NE 10'±



Signed by

*Kirk Breitels*

Date

2/6/96

Surveyor's Michigan License No.

30077