

W

FEB 14 1997

KENT COUNTY REMONUMENTATION

"other" code #18

COMMISSION

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

For corners in
KENT COUNTY
(County)

Located In:

Corner Code #

- 1. Public Land Survey T _____ R _____
T _____ R _____
T _____ R _____
T _____ R _____
- 2. Property Controlling S 5 T 8N R 11W Wit. Mon. on
in Section S _____ T _____ R _____ S. line Sec. 5
- 3. Miscellaneous S _____ T _____ R _____
Property in Section S _____ T _____ R _____

- 4. Lot No. _____, Recorded Plat _____
- 5. Private Claims _____

STATE OF MICHIGAN
 COUNTY OF KENT
 RECEIVED FOR RECORD
 96 OCT 18 AM 8:19
 REG. OF DEEDS
Lucy Stand
 9395

Register of Deeds Stamp & File Number

I, Kirk Breitels, in a field survey on Sept. 12, 19 96,

do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Professional Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

1837 GLO Not Set

P.A. 345 1990 KENT COUNTY

PEER APPROVED 3/7/96

CHAIRMAN *Harry Huber*

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Approximately May 1, 1996 I found the SE corner of Section 5 to be gone because of a house under construction is now occupying the location of the SE corner. Established a point on the S. line of Section 5 between the previously located SE corner and S 1/4 corner (Kent Co. Mon.).

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

- Set Standard Kent Co. Witness Monument on the S. line of Section 5
- Set Nail & KC Remon. tag top of W. post of guard rail S50°W 195.94'
- Set Nail & KC Remon. tag SW side Power Pole S30°E 37.10'
- Set Nail & KC Remon. tag top of E. post of guard rail N75°E 82.61'
- Capped Rerod (Chettleburgh) @ property corner N50°E 188.04'
- Set Nail & KC Remon. tag W. side (7' high) 16" Oak N15°E 90.22'
- SE corner of Sec. 5 (House at location) East 182.01'
- NW'ly edge of asph. road is SE'ly 1.5'±



Signed by *Kirk Breitels* 30077

Date 10/11/96

Surveyor's Michigan License No. _____

