

KENT COUNTY REMONUMENTATION

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

For corners in
KENT COUNTY
(County)

Located In:

Corner Code #

1. Public Land Survey

T R
T R
T R
T R

other #1

2. Property Controlling
in Section

S 6 T 8N R 12W
S T R

Wit. Mon. on
W. line

3. Miscellaneous

S T R
S T R

Sec. 6

Property in Section

4. Lot No. , Recorded Plat

5. Private Claims

STATE OF MICHIGAN
COUNTY OF KENT
RECEIVED FOR RECORD
95 AUG 29 AM 10:38
REG. OF DEEDS
6572

Register of Deeds Stamp & File Number

I, Kirk Breitels, in a field survey on July 31, 19 95

do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Professional Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

1837 GLO Brookfield Meander Corner Set
1992 LCRC #6572 Marshall Set Kent Co. Witness Mon.
W. line Sec. 6

The position of this corner was previously approved by the Kent County Remonumentation Peer Group, monumented by Chris Marschall on 10/9/92 and was recorded per LCRC #6572.

P.A. 345 1990 KENT COUNTY

PEER APPROVED 8/24/95

CHAIRMAN Harry Hubert

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found Standard Kent Co. Witness Mon. (Harrison) per witnesses from above LCRC as set by Chris Marschall at the described location.

LCRC #6572

Water Line S13°E 68.00' ±
Centerline Sign Post (steel) S06°W 50.99'
Nail & KC Remon. tag E. side 12" Twin Ash S16°W 68.18' (4' high)
Nail & KC Remon. tag NW side 26" Poplar S40°W 71.52' (3' high)
Nail & KC Remon. tag N. side 10" Ash S53°E 28.69' (3' high)
Nail & KC Remon. tag S. side 28" Willow S86°E 31.34' (4' high)
Corner is in center of grav. boat landing 1071.87' S. of West 1/4 corner Sec. 6
Buried 6" below grade

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Standard Kent Co. Witness Monument

Water Line S13°E 68' ±
Centerline Sign Post (steel) S06°W 50.9'
Nail & KC Remon. tag E. side 12" Twin Ash S16°W 68.25' (4' high)
Nail & KC Remon. tag NW side 26" Poplar S40°W 71.58' (3' high)
Nail & KC Remon. tag N. side 10" Ash S53°E 28.69' (3' high)
Nail & KC Remon. tag S. side 28" Willow S86°E 31.25' (4' high)
Buried 6" below grade



Signed by

Kirk Breitels

Date

8/24/95

Surveyor's Michigan License No. 30077