

SEP 13 1995

COMMISSION

KENT COUNTY REMONUMENTATION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

MAY 09 1996

COMMISSION

For corners in
KENT COUNTY
(County)

Located In:

Corner Code #

1. Public Land Survey

T R

T R

T R

T R

2. Property Controlling
in Section

S 7 T 8N R 12W

S T R

3. Miscellaneous

S T R

Property in Section

S T R

Other Code

#3

Wit. Mon. on

W. line

Sec. 7

REG. OF DEEDS

8681

95 AUG 29 AM 10:38

STATE OF MICHIGAN
COUNTY OF KENT
RECEIVED FOR RECORD

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat

5. Private Claims

I, Kirk Breitels, in a field survey on July 31, 19 95

do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Professional Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

1837 GLO Brookfield Meander Corner Set
1992 LCRC #6573 Marschall Set Kent Co. Witness Mon.
W. line Sec. 7

The position of this corner was previously approved by the Kent County Remonumentation Peer Group, monumented by Chris Marschall on 10/9/92 and was recorded per LCRC #6573.

PEER APPROVED

CHAIRMAN

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found Standard Kent Co. Witness Mon. (Harrison) per witnesses from above LCRC as set by Chris Marschall at the described location.

LCRC #6573

Nail & KC Remon. tag NE side 6" Ash	S52°E	56.04' (4' high)
3" x 1/2" "U" shaped channel (SE cor.) Iron	S66°E	45.29'
Edge of Water	North	19.00' ±
Nail & KC Remon. tag NE side 16" Ash	S59°E	29.86'
Nail & KC Remon. tag top end fence post (30° list to E.)	S85°E	35.74'
Nail & KC Remon. tag N. side 36" Poplar	S80°W	25.64'
Centerline of 4" steel dish antenna post	S59°W	129.78'

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Standard Kent Co. Witness Monument

Nail & KC Remon. tag NE side 6" Ash	S52°E	56.08' (4' high)
3" x 1/2" "U" shaped channel (SE cor.) Iron	S66°E	45.29'
Edge of Water	North	19' ±
Nail & KC Remon. tag NE side 16" Ash	S59°E	29.91'
Nail & KC Remon. tag top end fence post (45° list to E.)	S85°E	36.32'
Nail & KC Remon. tag N. side 36" Poplar	S80°W	25.64'
Centerline of 4" steel dish antenna post	S59°W	129.78'

Signed by

Date

30077

Surveyor's Michigan License No.

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971
REVISED MAY 14, 1975
REVISED JAN., 1983

	A	B	C	D	E	F	G	H	I	J	K	L	M
2													
3													
4													
5													
6													
7													
8													
9													
10													
11													
12													
13													

