

SURVEY & REMONUMENTATION

MAY 22 2000

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970 KENT COUNTY REMONUMENTATION

For corners in SECTION

Kent (County)	Located in: Courtland Township	Corner Code #
1. Public Land Survey	T 9N R 10W	J-11S
	T R	
	T R	
	T R	
2. Property Controlling in Section	S T R	2240.18 South Of J-11
	S T R	
3. Miscellaneous Property in Sec.	S T R	
	S T R	

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

"other" code
#6

REG. OF DEEDS

STATE OF MICHIGAN
COUNTY OF KENT
RECEIVED FOR RECORD
1999 OCT 15 AM 8:06

11355

Register of Deeds Stamp & File Number

I, Randy Kolehouse, in a field survey on February 3 19 99, do hereby certify that under requirements of P.A. 74 Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

J-11	1837	G.L.O. Notes	Cathcart	Set Post
	1996	L.C.R.C. #9409	Kirk Breitels	N/A
	1996	L.C.R.C. #9410	Kirk Breitels	Set K.C. Witness Monument

This corner was originally approved by the Kent County Remonumentation Peer Group and monumented by Kirk Breitels on 10/30/96 and was recorded per L.C.R.C. #9410.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

J-11 Found a Standard Kent County Witness Monument 410' ± North of Squires Street (gravel) running East and West, 6' ± East of a fence line running North and South, and 100' South of the South edge of a swamp per L.C.R.C.'s #9409 and #9410 as set by Kirk Breitels.

L.C.R.C. #9410

Nail & KC Remon. tag W. side 8" Cherry S10°W 15.67' (m. 15.71')
Nail & KC Remon. tag S. side 26" Oak S70°W 16.49' (m. 16.50')
Nail & KC Remon. tag S. side Fence cor. post S90°W 5.82' (m. 5.85')
Nail & KC Remon. tag E. side 6" Oak N10°E 14.69' (m. 14.77')
Nail & KC Remon tag SW side 16" Oak S40°E 49.65' (m. 49.63')
Capped Rerod (Exxel) - South 1.97' (m. 1.98')
Iron Pipe - SW 3.42' (M. 3.50')
S. Edge of Swamp - North 100'±/-

P.A. 345 1990 KENT COUNTY
PEER APPROVED 2/25/99
CHAIRMAN Randy Kolehouse

The selected location is accepted by me and is generally accepted by professional surveyors as the best available evidence of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

J-11 Standard Kent County Witness Monument

Nail & K.C. remon. tag on W side 8" Cherry S 10° W 15.71'
Nail & K.C. remon. tag on S side 26" Oak S 70° W 16.50'
Nail & K.C. remon. tag on S side fence cor. post S 90° W 5.85'
Nail & K.C. remon. tag on E side 6" Oak N 10° E 14.77'
Nail & K.C. remon. tag on SW side 16" Oak S 40° E 49.65'
Capped rerod (Exxel) South 1.93'
Iron pipe SW 3.50'

C/L of gravel road running E-W, South 410' ±
Fence line running N-S, West 6' ±
South edge of swamp, North 100' ±

Signed by Randy J. Kolehouse Date 9-27-99

WILLIAMS & WORKS

Surveyor's Michigan License No. 25854

