

MAY 22 2000

## SECTION

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970  
KENT COUNTY REMONUMENTATION

For corners in

Kent (County)	Located in: Courtland Township	Corner Code #
1. Public Land Survey	T 9N R 10W	J-11N
	T R	
	T R	
	T R	
2. Property Controlling In Section	S T R	1633.06 North Of J-11
	S T R	
3. Miscellaneous Property in Sec.	S T R	
	S T R	

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_  
5. Private Claims \_\_\_\_\_

I, Randy Kolehouse, in a field survey on February 3 19 99, do hereby certify that under requirements of P.A. 74 Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

**NOTE:** Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

## A. Description of original monument and accessories and/or subsequent restoration:

J-11	1837	G.L.O. Notes	Cathcart	Set Post
	1996	L.C.R.C. #9409	Kirk Breitels	N/A
	1996	L.C.R.C. #9412	Kirk Breitels	Set K.C. Witness Monument

This corner was originally approved by the Kent County Remonumentation Peer Group and monumented by Kirk Breitels on 10/30/96 and was recorded per L.C.R.C. #9412.

## B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

J-11 Found a Standard Kent County Witness Monument 3.5' West of a fence line running North and South, 150' ± North of the North edge of a swamp, per L.C.R.C.'s #9409 and #9412 as set by Kirk Breitels.

L.C.R.C. #9413

Nail & KC Remon. tag E. side 24" Cherry N15°E 41.21' (m. 41.20')  
Nail & KC Remon. tag NW side 12" Maple N55°E 68.56' (m. 68.54')  
Nail & KC Remon. tag NE side 20" Willow S35°E 49.37'  
N-S fence is East 3.5'±

P.A. 345 1990 KENT COUNTY  
PEER APPROVED 2/25/99

CHAIRMAN [Signature]

The selected location is accepted by me and is generally accepted by professional surveyors as the best available evidence of the position of the original corner.

## C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

## J-11 Standard Kent County Witness Monument

Nail & K.C. remon. tag on E side 24" Cherry N 15° E 41.20'  
Nail & K.C. remon. tag on NW side 12" Maple N 55° E 68.54"  
Nail & K.C. remon. tag on NE side 20" Willow S 35° E 49.37'  
Nail & K.C. remon. tag on top N side 18" Cherry S 40° E 27.01'  
Nail & K.C. remon. tag on W side 8" Oak S 05° E 57.50'  
Fence line running N-S, East 3.5'  
North edge of swamp, South 150' ±

Signed by [Signature] Date 9-7-99

WILLIAMS & WORKS

Surveyor's Michigan License No. 25854

