

SURVEY &
REMONUMENTATION

JAN 21 1998

SECTION

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Keweenaw

(County)

Located In:

Corner Code ##

1. Public Land Survey

T 57N R 29W

MC 14

T R

T R

T R

2. Property Controlling
in Section

S T R

S T R

3. Miscellaneous
Property in Sec.

S T R

S T R

4. Lot No. , Recorded Plat

5. Private Claims

REGISTER'S OFFICE

County of Keweenaw } SS

Received for Record, the 30th

Day of December A.D. 19 97

at 10:00 o'clock A.M. and Recorded

in Liber 1 of LCR

on page 172

Julie Carlson, Deputy

Register of Deeds

Register of Deeds Stamp & File Number

I, John Haataja, in a field survey on 11/7, 19 97,

do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

MC 14 Wood post set in 1847

Y. Pine 10" S66°W 83 LKS

Y. Pine 7" N63°W 107 LKS

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

MC 14 Reestablished in 1990 and recorded in LCR 1, Page 87, Keweenaw County Records. Reestablished MC and Section line from Monuments as called for in description of U.S. Lighthouse Parcel.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

MC 14 Set 1" pipe with brass cap

12" R. Pine N17°W 35.79'

16" R. Pine S84°E 2.09'

16" R. Pine S02°E 49.66'

12" W. Pine N76°W 38.48'

Ratified by Peer Group

In accordance with P.A. 345

Co. Rep. John Haataja

Date 10/15/97

Signed by

John I. Haataja

Date

12/30/1997

Surveyor's Michigan License No.

19833

| | A | B | C | D | E | F | G | H | I | J | K | L | M |
|----|----|----|----|----|----|----|---|---|---|---|---|---|---|
| 2 | 6 | 5 | 4 | 3 | 2 | 1 | | | | | | | |
| 3 | | | | | | | | | | | | | |
| 4 | 7 | 8 | 9 | 10 | 11 | 12 | | | | | | | |
| 5 | | | | | | | | | | | | | |
| 6 | 18 | 17 | 16 | 15 | 14 | 13 | | | | | | | |
| 7 | | | | | | | | | | | | | |
| 8 | 19 | 20 | 21 | 22 | 23 | 24 | | | | | | | |
| 9 | | | | | | | | | | | | | |
| 10 | 30 | 29 | 28 | 27 | 26 | 25 | | | | | | | |
| 11 | | | | | | | | | | | | | |
| 12 | 31 | 32 | 33 | 34 | 35 | 36 | | | | | | | |
| 13 | | | | | | | | | | | | | |

