

**SURVEY &
REMONUMENTATION**

FEB 18 1994

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970,

STATE OF MICHIGAN
COUNTY OF KALAMAZOO
RECEIVED FOR RECORD

93 DEC 29 AM 10 32

For corners in

COMMISSION

Kalamazoo
(County)

Located in:

Corner Code #

Ross Twp.

1. Public Land Survey

T 1 S R 9 W

L-9

T R

T R

T R

2. Property Controlling
in Section

S T R

S T R

3. Miscellaneous
Property in Sec.

S T R

S T R

James E. Boynton
CLERK-REGISTER

LIBER

1 PG 1049

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat

5. Private Claims

I, James E. Boynton, in a field survey on December 1, 19 93,
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the
current manual of survey instructions of the United States Department of the Interior, Bureau of Land
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a
Court of Law; established, re-established, monumented, re-monumented, recovered, found as
expressed below:

**NOTE: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.**

A. Description of original monument and accessories and/or subsequent restoration:

Post established by U.S. Government Deputy Surveyor John Mullitt in
1826. Corner remonumented in 1883 by F. Hodgeman, set standard
tile, accessories: Cherry S. N. 72 E. 06. Tile found in 1976
by Don Gilchrist, accessories: tile under log pile; twin 10" cherry
S. 80° W. 37.81'; 10" Cherry S. 20° W. 15.86'; 10" Sassafras N. 05° W. 7.42'.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found tile from 1976 witnesses

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

**RATIFIED
BY KALAMAZOO COUNTY
REMONUMENTATION
PEER GROUP
12-16-93**

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Found and accepted tile as carefull and faithfull perpetuation of
the original corner. Set standard sleeve over tile, new
witnesses: corner is 2' E. of N/S fence line; corner is
51' E. and 78' N. of N.E. corner of house #16503; 18" Cherry
N. 80° W. 30.16' to nail; 16" Cherry S. 20° W. 15.55' to nail;
16" Cherry S. 55° W. 38.67' to nail; 6" Maple North 36.77'
to nail.

Signed by

James E. Boynton

Date 12-9-93

Surveyor's Michigan License No.

29239