

FEB 08 1999

SECTION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

LIBER

2 PAGE 400

For corners in Alamo Twp.

Kalamazoo
(County)

Located in:

Corner Code #

1. Public Land Survey

T1S R12W

B-01

2. Property Controlling
in Section

S

T R

3. Miscellaneous
Property in Sec.

S

T R

4. Lot No. , Recorded Plat

5. Private Claims

I, Robert E. Snell, in a field survey on Sept. 30, 19 98 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2													
3													
4													
5													
6													
7													
8													
9													
10													
11													
12													
13													

A. Description of original monument and accessories and/or subsequent restoration:

This corner not set by original government surveyors.

1875: E. Strong, County Surveyor; set stake from Otsego corner "Stake, Beech 14" S. 6 $\frac{1}{2}$ ° W. 9 lks. found Allegan 1/4 and made the jog the same as I found it at the NEC by actual measure."

RATIFIED
BY KALAMAZOO COUNTY
REMONUMENTATION
PEER GROUP
11/19/98 R. E. Snell

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

1975: Gove Associates, D. Middleton, RLS#16049; ran North line of Section 6, Alamo did not set North 1/4 post.

1998: Set North 1/4 post by running North line Section 6 from NW cor. (Harrison Monument) over South 1/4 post of Section 32, Otsego Twp. using 85.00' jog as determined by Ed Strong, County Surveyor in 1875 survey by proration of E. Strong measure.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

B-01: North 1/4 post, Section 6, T. 1 S., R. 12 W., ratified by the Kalamazoo County Remonumentation Program Peer Group on November 11, 1998 and is accepted as a careful and faithful re-establishment of the position of the corner established by Ed Strong, County Surveyor in 1875. See "B" above. Placed 30" Harrison monument.

PK Nail in North Side
PK Nail in North Side
PK Nail in West Side
PK Nail in South Side

30" Maple
28" Maple
12" Maple
15" Maple

S. 85° W. 5.83'
S. 85° E. 24.37'
N. 05° E. 34.60'
N. 75° E. 51.90'

Signed by

Robert E. Snell

Date

12-18-98

Surveyor's Michigan License No.

9734