

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Kalamazoo

(County)

Charleston Section 30

Located in:

Corner Code #

1. Public Land Survey

T 2 S R 9 W

B-9

2. Property Controlling
in Section

S T R

3. Miscellaneous
Property in Sec.

S T R

4. Lot No. , Recorded Plat

5. Private Claims

CLERK - REGISTER

STATE OF MICHIGAN
COUNTY OF KALAMAZOO
RECEIVED FOR RECORD
JAN 15 PM 1 37

LIBER

1 PG 1104

Register of Deeds Stamp & File Number

I, Robert E. Snell, in a field survey on January 17, 1994,

do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

Original corner established by U.S. Government Survey-1826. Set Post

Wh. Oak 9" North 57°-E 11 Lks (7.26')

Wh. Oak 10" South 70°-W 43 Lks (28.38')

1883-F. Hodgeman County Surveyor-found stake intact by two U.S. bearing trees standing.
Bored 3' and filled bottom with small stone and put two one-foot earthen post over.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found solid clay tile near surface.

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9	25	26	27	28	29	30							
10													
11													
12	31	32	33	34	35	36							
13													

RATIFIED
BY KALAMAZOO COUNTY
REMONUMENTATION
PEER GROUP

1-20-94

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

B-9 North 1/4 post Section 30, T. 2 S., R. 9 W., Ratified by Kalamazoo County Remonumentation Program Peer Group on January 20, 1994. Found solid clay tile as called for in remonumentation survey of 1883 by F. Hodgeman and is accepted as a careful and faithful perpetuation of the original corners position. Set remonumentation sleeve over tile.

Nail/Tab in N side 23" Maple N 10° E 25.15'

PK Nail in N side 19" Maple S 55° E 58.98'

PK Nail in W side 19" Beech S 40° W 26.06'

Nail in S side Abandoned PP S 70° W 1.60'

Nail in S side RR tie Fence corner N 60° W 9.38'

Signed by

Robert E. Snell

Date

1-15-94

Surveyor's Michigan License No. 9734